



\$10,000

**BLOCKBUSTER
SWEEPSTAKES**

Details p.28

WOODCRAFT[®]

Projects, Techniques, and Products

magazine

Hand Plane Showcase *p.41*

MORE PROJECTS

- *Holiday Carousel*
- *Toy Bulldozer*
- *Votive Candle
Stands*

PLUS...

- **10** *Trailblazing
Tools*
- **10** *Essential
Sharpening Tips*
- **10** *Best-Ever
Tips & Tricks*



VOL. 11/NO. 62 DEC/JAN 15

\$6.99



Display until January 27, 2015

HOW CAN THE BEST GET BETTER?

Item# P410

Introducing the Next Generation Premier Fusion

**with Radical New
Fusion Trio Tooth Design**

Now the most technologically advanced general purpose blade on the market includes an one-of-a-kind tooth geometry with 30 degree Hi-ATB, a double side grind design, and an Axial Shear Face Grind to produce the ultimate polished finish with minimal resistance! Whether you're ripping or crosscutting, the next generation Premier Fusion blade is the best for flawless cuts in laminates, melamine, veneered plywoods, hardwoods, softwoods, and thick stock lumber.

NEW FUSION TRIO TOOTH GEOMETRY

DOUBLE SIDE GRIND
design for delivering
polished cross cuts

30° Hi-ATB
for slicing through
plywood and melamine

AXIAL SHEAR FACE GRIND
that glides through wood
and sheet goods with
minimal resistance



For more information visit: www.freudtools.com/premierfusion

To find a Freud Certified Sharpener near you visit: www.freudtools.com/sharpen

©2014. Red saw blades are a registered trademark of Freud America, Inc. (US) 1-800-334-4107

\$1,097


INTRODUCING **THE UNEXPECTED** 14|TWE LVE



Go to your Woodcraft dealer today to see why everyone is raving about the 14|Twelve bandsaw



- 115 Volt, 1 $\frac{3}{4}$ HP
- Oversized Cast Trunnion
- Laguna Ceramic Guides
- World Class Fit & Finish
- Worm Gear Rack & Pinion
- Dynamically Balanced Cast Wheels
- Enclosed Stand, Hi/Low Rip Fence
- Optional Wheel System & Blades



*SHOWN WITH OPTIONAL INDUSTRIAL FLOOD LIGHT

LAGUNA
LAGUNATOOLS.COM





Grizzly Industrial

PURVEYORS OF FINE MACHINERY®, SINCE 1983!

- OVER A MILLION SQUARE FEET PACKED TO THE RAFTERS WITH MACHINERY & TOOLS
- 2 OVERSEAS QUALITY CONTROL OFFICES STAFFED WITH QUALIFIED GRIZZLY ENGINEERS
- HUGE PARTS FACILITY WITH OVER 1 MILLION PARTS IN STOCK AT ALL TIMES
- 24 HOUR ORDERING BY PHONE OR ONLINE • MOST ORDERS SHIP THE SAME DAY



30TH ANNIVERSARY SPECIAL EDITION 14" DELUXE BANDSAW



- Motor: 1 HP, 110V/220V, single-phase, TEFC
- Precision-ground cast iron table size: 14" sq.
- Table tilt: 45° R, 10° L
- Cutting capacity/throat: 13½"
- Max. cutting height: 6"
- Blade size: 92½"-93½" L (1½"-¾" W)
- Blade speeds: 1800 & 3100 FPM
- Approx. shipping weight: 247 lbs.



**CAST
IRON
WHEELS**

MADE IN TAIWAN

G0555LANV ~~\$545⁰⁰~~
SALE \$445⁰⁰



30TH ANNIVERSARY SPECIAL EDITION 17" BANDSAW



- Motor: 2 HP, 110V/220V, single-phase, TEFC
- Precision-ground cast iron table size: 17" sq.
- Table tilt: 45° R, 10° L
- Cutting capacity/throat: 16¼"
- Max. cutting height: 12½"
- Blade size: 131½" L (1½"-1" W)
- Blade speeds: 1700 & 3500 FPM
- Quick-release blade tension lever
- Approx. shipping weight: 342 lbs.

MADE IN TAIWAN

INCLUDES DELUXE
EXTRUDED ALUMINUM
FENCE, MITER GAUGE &
½" BLADE

G0513ANV ~~\$895⁰⁰~~
SALE \$825⁰⁰



ULTIMATE 14" BANDSAW



- Motor: 1 HP, 110V/220V, single-phase, TEFC
- Precision-ground cast iron table size: 14" sq.
- Table tilt: 45° R, 15° L
- Cutting capacity/throat: 13½"
- Max. cutting height: 6"
- Blade size: 92½"-93½" L (1½"-¾" W)
- Blade speeds: 1500 & 3200 FPM
- Approx. shipping weight: 196 lbs.

MADE IN TAIWAN



G0555P ~~\$545⁰⁰~~ **ONLY \$525⁰⁰**



17" 2 HP HEAVY-DUTY BANDSAW



- Motor: 2 HP, 110V/220V, single-phase, TEFC
- Precision-ground cast iron table size: 17" sq.
- Table tilt: 45° R, 10° L
- Cutting capacity/throat: 16¼"
- Max. cutting height: 12½"
- Blade size: 131½" L (1½"-1" W)
- Blade speeds: 1700 & 3500 FPM
- Quick-release blade tension lever
- Approx. shipping weight: 346 lbs.

INCLUDES DELUXE EXTRUDED
ALUMINUM FENCE, MITER GAUGE &
½" BLADE

MADE IN TAIWAN



G0513P ~~\$895⁰⁰~~ **ONLY \$875⁰⁰**



19" HEAVY-DUTY BANDSAWS



- Motor: 3 HP, 220V, single-phase, TEFC
- Precision-ground cast iron table size: 26¾" x 19"
- Table tilt: 45° R, 5° L
- Cutting capacity/throat: 18½"
- Max. cutting height: 12"
- Blade size: 143" L (1½"-1¼" W)
- Blade speeds: 1700 & 3500 FPM
- Approx. shipping weight: 460 lbs.

**EXTREME
SERIES**

DELUXE RESAW FENCE
INCLUDED

MADE IN TAIWAN



G0514X
~~\$1495⁰⁰~~ **SALE \$1450⁰⁰**
ALSO AVAILABLE G0514XF W/ FOOT BRAKE
ONLY \$1425⁰⁰



10" LEFT-TILTING CONTRACTOR-STYLE TABLE SAW with Riving Knife

- Motor: 1½ HP, 110V/220V, single-phase
- Precision-ground cast iron table with wings
- Table size: 25¼" x 40" • Arbor: 5"
- Arbor speed: 4000 RPM
- Capacity: 3¼" @ 90°, 2¼" @ 45°
- Rip capacity: 30" R, 12" L
- Approx. shipping weight: 208 lbs.

MADE IN TAIWAN

FREE 10"
CARBIDE-
TIPPED BLADE



G0732 ~~\$795⁰⁰~~ **SALE \$650⁰⁰**



10" HYBRID TABLE SAW



**BEAUTIFUL
WHITE COLOR!**



- Motor: 2 HP, 110V/220V, single-phase
- Precision-ground cast iron table with wings measures: 27" x 40"
- Arbor: 5" • Arbor speed: 3850 RPM
- Capacity: 3¼" @ 90°, 2¼" @ 45°
- Rip capacity: 30" R, 12" L
- Quick-change riving knife
- Cast iron trunnions
- Approx. shipping weight: 416 lbs.



INCLUDES BOTH REGULAR
& DADO BLADE INSERTS

G0715P **ONLY \$795⁰⁰**



10" LEFT-TILTING TABLE SAWS with Riving Knife & Cast Iron Router Table

- Motor: 3 HP or 5 HP, 240V, single-phase
- Precision-ground cast iron table size with wings: 27" x 48"
- Arbor: 5"
- Cutting capacity: 25½" R, 8" L
- Max. depth of cut: 3" @ 90°, 2¼" @ 45°
- Approx. shipping weight: 550 lbs.

MADE IN TAIWAN

G1023RLW 3 HP ~~\$1360⁰⁰~~
ONLY \$1325⁰⁰
G1023RLWX 5 HP ~~\$1395⁰⁰~~
ONLY \$1350⁰⁰



PRICING CODE
14WOODC
MENTION THIS CODE
WHEN PLACING YOUR ORDER
16660

VIEW VIDEOS AT
grizzly.com

1-800-523-4777

3 GREAT SHOWROOMS!
BELLINGHAM, WA MUNCY, PA SPRINGFIELD, MO

TECHNICAL SERVICE:
570-546-9663
FAX: 800-438-5901

Christmas Sale

November 1st - December 31st

PLEASE GO TO **GRIZZLY.COM**® TO SEE ALL SALE PRICES



GRIZZLY GIFT CERTIFICATES TAKE THE GUESSWORK OUT OF GIVING!



10" CABINET TABLE SAW

with Riving Knife & Extension Rails

- Motor: 3 HP, 220V, single-phase
- Precision-ground cast iron table
- Table size with extension: 27" x 74 3/4"
- Arbor: 3/8" • Arbor speed: 4300 RPM
- Max. depth of cut: 3 1/8" @ 90°, 2 1/8" @ 45°
- Max. rip capacity: 50" R, 12" L
- Max. dado width: 1 3/8"
- Approx. shipping weight: 557 lbs.



3 HP LEESON® MOTOR!

FREE 10" CARBIDE-TIPPED BLADE



G0691 ~~\$1595.00~~ ONLY **\$1525.00**



FLOOR-MODEL OSCILLATING SANDER

- Motor: 1 HP, 110V, single-phase, 6.9A
- 1725 RPM spindle speed (no load)
- 19 1/8" diameter cast iron table
- Spindle oscillation: 52 OPM
- 3 Rubber sanding drums: 3/4" x 4 1/2", 2" x 9", and 3" x 9"
- 3 Sanding sleeves: 3/4" x 4 1/2", 2" x 9", and 3" x 9"
- Table inserts: 6
- Floor to table height: 36 3/4"
- Dust port: 2"
- Toggle ON/OFF safety switch with locking tab
- Includes two wrenches for easy spindle changes
- Approximate shipping weight: 143 lbs.



T26418 ~~\$475.00~~ SALE **\$425.00**



12" JOINTER/PLANER COMBINATION MACHINES

- Motor: 5 HP, 220V, single-phase
- Jointer table size: 14" x 59 1/2"
- Cutterhead dia.: 3 1/8"
- Cutterhead speed: 5034 RPM
- Max. jointer depth of cut: 1/8"
- Max. width of cut: 12"
- Planer feed rate: 22 FPM
- Max. planer depth of cut: 1/8"
- Max. planer cutting height: 8"
- Planer table size: 12 1/4" x 23 1/2"
- Approx. shipping weight: 704 lbs.

NEW END-MOUNTED FENCE



MADE IN TAIWAN

CARBIDE INSERT SPIRAL CUTTERHEAD!



WITH SPIRAL CUTTERHEAD

G0634XP ~~\$2350.00~~ ONLY **\$2295.00**

ALSO AVAILABLE IN GRIZZLY GREEN

G0633 JOINTER/PLANER WITH HSS KNIVES ~~\$2050.00~~ ONLY **\$1995.00**

G0634Z W/SPIRAL CUTTERHEAD ~~\$2595.00~~ ONLY **\$2550.00**

HEAVY-DUTY MORTISER WITH STAND

- Motor: 1 1/2 HP, 110V/220V, single-phase, TEFC, 1725 RPM, prewired 110V
- Amps: 14A at 110V, 7A at 220V
- Table size: 19" x 12 1/2" • Vertical spindle travel: 9"
- Head vertical travel: 3" • Table longitudinal travel: 14 1/2"
- Table cross travel: 3" • Column tilt: ±30°
- Fence angle: 0-30° • Chisel capacity: 1/4"-1 1/2"
- Maximum chisel stroke: 6 1/4"
- Maximum workpiece width: 9"
- Chuck capacity: 1/2"
- Collar size: 5/8" and 3/4"
- Spindle speed: 1725 RPM
- Overall size: 36" wide x 71" high x 24" deep
- Approximate shipping weight: 356 lbs.

STAND INCLUDED

MADE IN TAIWAN



G0448 ONLY **\$1495.00**

CYCLONE DUST COLLECTOR

- Motor: 1 1/2 HP, 110V/220V, single-phase, TEFC, 3450 RPM
- Air suction capacity: 775 CFM
- Static pressure at rated CFM: 1.80"
- Intake port: 6" with included 5" optional port
- Impeller: 13 1/2"
- Height: 65 1/2"
- Built-in remote control switch
- Approx. shipping weight: 210 lbs.

MADE IN TAIWAN



BEAUTIFUL WHITE COLOR!

FULLY MOBILE WITH BUILT-IN CASTERS



PLEATED FILTER IS PROTECTED BY A STEEL CAGE



ONLY 65 1/2" TALL!



G0703P ~~\$825.00~~ ONLY **\$795.00**

24" DRUM SANDER

- Motor: 5 HP, 220V, single-phase drum motor drives 2 aluminum sanding drums
- Surface speed of drum: 2300 FPM
- Handles stock up to 23 1/2" wide and 4 1/4" thick
- 1/4 HP Conveyor motor provides 11 FPM feed rate
- Sandpaper installs easily onto the drums
- Sanding drum size: 6"
- All steel and ball bearing construction
- Two 4" dust ports for easy hook-up to a collection system
- State-of-the-art computer balanced drums
- Powder-coated paint
- Approximate shipping weight: 442 lbs.



G1066R ~~\$1695.00~~ SALE **\$1595.00**



VARIABLE SPEED PLANER/ MOULDER

- Motor: 2 HP, 240V, single-phase, 12 Amps
- Precision-ground cast iron table and wings
- Maximum cutting width: 7"
- Maximum planing height: 7 1/2"
- Maximum planing depth: 1/8"
- Maximum moulding depth: 3/4"
- Feed rate: Variable • Cutterhead type: Square
- Knife size: 7 7/8" x 1 1/2" x 1/4" HSS
- Cutterhead speed: 7000 RPM • 4" dust port
- Rubberized steel feed rollers • Powder-coated finish
- Approx. shipping weight: 324 lbs.



MADE IN TAIWAN



W1812 ~~\$1650.00~~ SALE **\$1525.00**

2 HP DUST COLLECTOR with Aluminum Impeller

- Motor: 2HP, 240V, single-phase, 3450 RPM
- Motor amp draw: 9 Amps
- Air suction capacity: 1550 CFM
- Static pressure: 11"
- 6" inlet has removable "Y" fitting with two 4" openings
- Impeller: 12 1/2" balanced cast aluminum
- Bag capacity: 5.7 cubic feet
- Standard bag filtration: 2.5 micron
- Portable base size: 21 1/4" x 33 1/2"
- Bag size (dia. x depth): 19 1/2" x 33"
- Powder-coated finish
- Height with bags inflated: 78"
- Approx. shipping weight: 122 lbs.



MADE IN TAIWAN

W1049 2 STAGE CYCLONE SEPARATOR FREE WITH PURCHASE

MADE IN ISO 9001 FACTORY!

G10292P ~~\$335.00~~ ONLY **\$325.00**



grizzly.com®

OVER 15,000 PRODUCTS ONLINE!

FOLLOW US:





30 Arts & Crafts Votive Candle Stands

Use simple frame-and-panel construction to build one or more of these tabletop accents. Made from quartersawn and riftsawn white oak, their heights are 7¼", 8 ½", and 9¾".



51 Tough-Enough Bulldozer

Make this hardworking earthmover for the busy road builder in the family. It features a lifting blade for easy maneuvering and treads that lay down tracks in sand or on carpet.

60 Holiday Carousel

Add a warm glow to the holiday season with this eye-catching decoration. The heat from four lit candles spins the propeller, causing the winter scene to rotate. Find the needed patterns inside.



41 Windowed Hand Plane Cabinet

Protect your planes in this custom showcase. A deep shelf provides at-the-ready storage for smoothers, while the divided ramps organize longer tools. Stash related supplies in the drawers.



FIRST IN SO MANY THINGS THAT MATTER.



The heaviest. The most powerful. The only saw with an active safety system and 99% dust collection.
Is it any wonder it has been the number one saw for a decade? Discover the pride of ownership.


Visit SawStop.com/10

\$200+ in FREE Essentials
Oct 1 - Dec 31, 2014

Buy a new SawStop Industrial Cabinet Saw and receive a FREE Standard Brake Cartridge and
TWO FREE SawStop Titanium Blades! Visit Sawstop.com/10 for details.



Contents: Tools & Techniques



14 10 All-Time Best Tips & Tricks

Feast on this choice roundup of clever reader submissions, and find several ideas you can use right now.



24 10 Game-Changing Innovations

See the tools and technologies that have made the most significant impacts on the woodworking world in the last decade.

35 10 Essential Sharpening Tricks

Discover craftsman Andy Rae's shop-proven sharpening tips for grinding, honing, and polishing the cutting edges of chisels and plane blades.



69 Specialty Chisels

Check out these hand tool specialists that can help you to make quicker work of a variety of chiseling challenges.

Departments

8 Cutting In

74 Woodsense
Red Oak

12 Mailbox





***“American Made for
the American Woodworker”***

2-Piece Stile & Rail Door Sets

Proven design allows you to make full-sized stile and rail frames on your router table for raised panels, plywood panels, even glass panel doors.

- Interlocking Profile And Panel Groove Cut In One Pass
- Simply Switch Bits To Change From Cutting Stiles To Cutting Rails
- No Extra Components Are Required For Glass Panel Doors
- Conversion Kit Available For Undersized Plywood Panels
- Choose From Six Distinct Profiles To Match Your Personal Style

6001	Roundover	6004	Straight
6002	Ogee	6005	Traditional
6003	Bead	6006	Classical

6000X 7/32" Plywood Conversion Kit



Two Great Items Available at **WOODCRAFT** • Visit woodcraft.com Or Call 800-225-1153




“ULTIMATE” Flush Trim/Pattern Router Bits

“ULTIMATE” Trim Bits are perfect when working with templates or when using a router to flush trim matching wood surfaces. Whiteside’s compression spiral design, along with a ball bearing guide, makes this bit easy to use in the router and produces a superior quality trimmed edge. The “ULTIMATE” Trim series brings industrial engineered bits, previously manufactured for CNC machines, right into your shop.

7/8" Diameter x 1 1/8" Cut Length
x 1/2" Shank

UDFT9112 (A) Flush Trim
UDP9112 (B) Pattern/Plunge
UPC9112 (C) Combination



Whiteside Machine Co., Claremont, North Carolina
800-225-3982 • whitesiderouterbits.com



Cutting In



ENTER FOR
A CHANCE TO
WIN
AS WE CELEBRATE OUR
10TH
ANNIVERSARY
ISSUE!

The dedicated staff at *Woodcraft Magazine* is proud to present to you our Dec/Jan 2014/15 issue of the magazine, a milestone event that marks 10 successful years of serving your woodworking needs. And whether you found us at the newsstand, at a Woodcraft store, or through a direct-mail subscription drive, we'd like to thank you for your support.

When we planned this issue, we wanted to pursue stories that tied in with the best of what *Woodcraft Magazine* has to offer in terms of engaging and useful content. We kick it off with a classic hand plane cabinet (page 41), a signature project that lets those visiting your shop know that they've entered the sanctuary of a quality woodworker.

We also got playful with the "10" concept behind our anniversary issue. You may enjoy reading the 10 best tips and tricks to ever run in the magazine (page 14) or reviewing the 10 most game-changing innovations in the woodworking product world over the last 10 years (page 24).

Finally, while 10th anniversaries are often marked by gifts in tin and aluminum, we've changed it somewhat by offering outstanding prizes in wood and steel. All you need to do is enter our **\$10,000 Blockbuster Sweepstakes** for a chance to win one. Included is our Grand Prize—a leather-cushioned Morris Chair (a former cover project) and matching Ottoman. This is followed by a Jet lathe and set of Easy Wood turning tools; a Rikon bandsaw; and 15 other worthy prizes. (See the details in our advertisement on page 28.) We'll announce our winners on February 16, 2015, and name names in the April/May issue. Best of luck to each of you.

WOODCRAFT[®] magazine

Dec/Jan 2015

Volume 11, Issue 62

Editor In Chief
Senior Editors

Jim Harrold
Paul Anthony
Joe Hurst-Wajszczuk

Art Director
Graphic Designer

Chad McClung
Shayne Hiles

Copy Editor, Proofreader
Sharon Hambrick

Contributing Consultants/
Craftsmen/Project Designers
Craig Bentzley, Marlen Kemmet
Geoff Noden, Larry Osborn, Andy Rae,
Jeff Slahor, Pete Stephano, Tom Whalley

Publisher Gary Lombard

Advertising Sales Manager Vic Lombard

Circulation Support Kim McLaughlin

Advertising/Administrative
Coordinator Kiah Harpool

Circulation
Circulation Specialists, Inc.

Subscriptions
U.S. and Canada, \$19.97 for one year
Single copy, \$6.99
customer_service@woodcraftmagazine.com
(800) 542-9125

Contact Us
Woodcraft Magazine
4420 Emerson Avenue, Suite A
P.O. Box 7020
Parkersburg, WV 26102-7020
(800) 542-9125 Fax: (304) 420-9840
Email: editor@woodcraftmagazine.com
Online: woodcraftmagazine.com

Woodcraft Magazine (ISSN:1553.2461, USPS 024-953) is published in January, March, May, July, September and November and printed in the United States by Woodcraft Supply, LLC, 4420 Emerson Ave., Suite A, Parkersburg, WV 26104. Tel: (304) 485-2647. Periodical Postage paid at Parkersburg, WV, and at additional mailing offices. Copyright 2014 by Woodcraft Supply, LLC. All rights reserved. POSTMASTER: Send address changes to *Woodcraft Magazine*, P.O. Box 7020, Parkersburg, WV 26102-7020. Canada Post: Publications Mail Agreement #40612608. Canada Returns to be sent to Pitney Bowes, P.O. Box 25542, London, ON N6C 6B2

Printed in the USA

Safety First! Working wood can be dangerous. Always make shop safety your first priority by reading and following the recommendations of your machine owner's manuals, using appropriate guards and safety devices, and maintaining all your tools properly. Use adequate sight and hearing protection. Please note that for purposes of illustrative clarity, guards and other safety devices may be removed from tools shown in photographs and illustrations in this publication.

King Arthur's Tools Congratulates Another Visionary – Woodcraft Magazine On Their 10th Anniversary!

*"King Arthur's Tools
are an extension
of your eye."*

– Jeffro Uitto
jeffrouitto.com

LANCELOT® saw chain cutters feature consecutive left and right teeth, not separated by skip links common to chain saw blades, with twice the teeth. Lancelot® cuts in any direction.

22 Tooth & 14 Tooth Blades
Available In 3 Center Hole Sizes
Tandem Combos w/Universal Nut
Fits 4 1/2" Angle Grinders

HOLEY GALAHAD® carbide sanders open a "Window To Your Work." Experience power and increased productivity by being able to continually see through the spinning disc to your work surface.

Coarse, Medium & Fine Grits
Round Or Flat Surface Profiles
Durable Tungsten Carbide
Fits 4 1/2" Angle Grinders



Tools To Bring Your Vision To Reality

800-942-1300 • katools.com

Face it!



This is *the* cutting-edge Face Frame Jig System

Clamp, drill and fasten in one simple set-up!

This easy-to-use system increases productivity by simplifying fabrication of face frames, cabinet doors and other woodworking assemblies. In one simple operation, you can align, securely clamp, bore pocket holes and screw components together.

Now available through Woodcraft Supply:
woodcraft.com/generaltools



Specialty Tools & Instruments

Precision, Specialty & Innovation...since 1922



General Tools & Instruments



GeneralToolsNYC

General Tools & Instruments 80 White Street, New York, NY 10013 | tel 800-697-8665 | www.generaltools.com

Check out General's full line of woodworking jigs



Crown King Crown Molding Jig

helps you make seamless, perfectly mitered interior and exterior corner joints.


#880



The E•Z Pro™ Mortise & Tenon Jig

lets you make perfectly matched mortise & tenon joints with one jig.


#870



The E•Z Pro™ Dovetail Jig

lets you make dovetail and box joints – through or half-blind.

#861



The E•Z Pro™ Pocket Hole Jig

has everything you need to make flush, corner and angle pocket hole joints.

#850



The E•Z Pro™ Doweling Jig

lets you make perfectly aligned dowel joints every time.

#851



Readers reflect

In my editor's column in the previous issue, I asked readers to tell me how the magazine has made a positive difference in their lives, now that we've completed 10 successful years of publishing. Here is a sampling of their responses.
—Jim Harrold, editor in chief

I am a hobbyist woodworker and was instantly attracted to your bagel slicer in the Feb/ March 2014 issue. A professional violinist friend had her career destroyed by nerve and tendon damage when slicing a bagel she had held in her hand. Your design provides a much safer approach. I have made and

given away a dozen to family, friends, and neighbors.

—Hank Burchard,
Amherst, Virginia

I look forward to each new issue of *Woodcraft Magazine*, but especially the ones closest to Christmas. There are always great projects, many that will become presents for family and friends.

—Lewis Kauffman,
Chambersburg, Pennsylvania

Whenever I receive my new issue of *Woodcraft Magazine*, it always inspires me to re-start my interest in lathe turning

and finish up other projects I started from the last issue. The magazine has been a big part of my retirement and enjoyment.

—Dan Baxendale,
Livonia, Michigan

Errata

As careful as we are, errors occasionally find their way into articles. If you spy an apparent mistake, particularly in a project article, please visit woodcraftmagazine.com and click on "corrections."



Picnic table pointers

I have completed the octagon picnic table from the April/ May 2014 issue and plan to build another. Already it has generated some interest—a neighbor and another family member are hinting about getting the plans and/or my help too. As you can see above, I used pressure-treated lumber. The table is heavy and strong. You can walk in and sit down rather than climb in. Two adjacent sections of seat boards can be easily changed/cut shorter to allow for wheelchair access! All in all, I liked building it!

—Doug Farquhar, Sauble Beach, Ontario

Doug, some worthy ideas. Thanks.

—Jim Harrold, editor in chief

A mighty fundraiser, the pen

As a teacher of pen turning classes at the Cleveland Woodcraft store, I recently was involved in a church fundraiser that proved quite successful and worth adopting. It so happened that the church's organ (over 50 years old) fell into disrepair and was declared beyond restoring. Its wood was destined for the landfill. I spoke with the pastor and requested that the wood be set aside. Then, this past August, I did a pen turning demo for the men's group at my church. Here, I let them in on the surprise: the resulting pen, which I passed around, had been made from the old organ's salvaged wood. That sparked a fundraiser idea where we would make pens and sell



them for \$30 each. Woodcraft store owner Mike Novak gave us a discount on the pen kits. In short order, we presented the pastor with a check for over \$1,300.00.
—Dave Sanborn, Cleveland, Ohio

Chime in

Have comments about the magazine, questions about an article, or something to share with your fellow Woodcraft Magazine readers? Send an email to editor@woodcraftmagazine.com or a letter to **Woodcraft Magazine, PO Box 7020, Parkersburg, WV 26102.**

Add a TV Lift To Your Design



WhisperLift II TV Lift

- Easy to install
- RF remote control operation
- Holds up to 60" flat screen TV


touchstone
Smart Furniture. Beautiful Solution.

Retail \$699.00
Special \$449.00



ORDER ONLINE www.TouchstoneHomeProducts.com OR CALL 800-215-1990

New!



WOODCRAFT
magazine
Volume 1
The 1st 5 Years

Over **100**
projects for
your shop
and home.

PLUS...

151 Tips and Tricks
130 Hot New Tools
250 Techniques



At a great low price!

Imagine owning the first
31 issues of Woodcraft
Magazine for just **\$19.99**.
With this new CD, now you
can. The CD features a PDF
format for ease of use on
most computers.

Call today **1-800-225-1153**
or go online at
www.woodcraft.com




Best of Tips and Tricks

Over the past 10 years, readers have shared some great techniques, jigs, and shop accessories in our "Tips and Tricks" column. Every issue, we award "Top Tip" status (including a special prize) to the most useful or clever tip of the bunch. For your pleasure, we have compiled here what we consider to be the best of the best from the past decade. Enjoy!

Pegboard panel pullouts

When outfitting my new shop, I needed a way to store and organize my hand tools, so I stole this storage design from my friend Bob Della-Rovere in Mesa, Arizona. The setup consists of simple $\frac{3}{4}$ "-thick frames covered on both faces with pegboard and mounted vertically in a cabinet on full-extension drawer slides screwed to cleats. You could fix the cleats directly to a cabinet top and bottom, but I decided to mount them to a "case insert," which I then slipped into the cabinet opening after assembling the entire unit. This system works great for storing lots of tools in a compact area.

—Bob Kellenberger, Fairview, Texas



Keep the Tradition Alive
Leigh Jigs make Dovetails perfectly and easily every time.

Share a Slick Tip. Win Cash or a Prize!

Here's your chance to help someone become a better woodworker and get rewarded for the effort. The winner of next issue's **Top Tip** award will receive a **Woodcraft Gift Card worth \$250**. All others will receive **\$125** for a published illustrated tip, or **\$75** for a non-illustrated tip. Published tips become the property of *Woodcraft Magazine*. Send your ideas to:


Tips & Tricks, Woodcraft Magazine, P.O. Box 7020, Parkersburg, WV 26102-7020 or visit **woodcraftmagazine.com**, and click on "Submit Tips." Important: Please include your phone number, as an editor may need to call you if your trick is considered for publication.

Triangle marking system


I was in my shop trying to organize a jumble of cabinet parts, when a friend dropped by and showed me an old layout trick that has since saved me lots of time and confusion. After parts are cut to size, and before you lay out any joints, select the “show” face of each piece, orient it for best grain composition, and then organize the pieces on your bench in their desired relation to each other. Now it’s a simple matter of pressing the pieces together and striking a few lines across their faces to create a triangle, as shown in the drawings. A glance at the markings immediately identifies the “show” face, the top, the bottom, and the left- and right-hand sides of each piece. To identify multiples, strike additional lines that extend across the mating pieces.

—Gary Goldthwaite, Indianapolis, Indiana


Frames/cases




Legs



Panels/drawer fronts



Aprons/drawers (top view)



Additional lines indicate multiples.

Forrest Blades

Experienced woodworkers know that Forrest blades are ideal for remodeling high-end kitchens and baths.

Forrest blades deliver smooth, quiet cuts *without* splintering, scratching, or tearouts. Our proprietary manufacturing process, hand straightening, and unique grade of C-4 micrograin carbide produce blades that are perfect for cabinets, countertops, and flooring. In fact, independent tests rate us #1 for rip cuts and crosscuts.

“Your blades are without question the best by miles, and I have tried them all.”


Bob Jensen, Fridley, MN

Forrest Quality Shows



Duraline Hi-AT—

Great for cutting two-sided veneers and low pressure laminates.



Woodworker II—

Best rated, all-purpose blade for rips and crosscuts.

Order from any Forrest dealer or retailer, online, or by calling directly. Our blades are manufactured in the U.S.A. and come with our 30-day, money-back guarantee.

© 2014 Forrest Manufacturing Code WC



FORREST

The First Choice of Serious Woodworkers Since 1946


www.ForrestBlades.com

1-800-733-7111 (In NJ, 973-473-5236)

Wall-mounted lamp arm

At my shop workstations, I like to use swing-arm lamps for adjustable task lighting. For convenience, I mount the lamp on a wooden arm that swings out from a nearby wall. Sometimes, a single arm does the trick, but when I need more reach and flexibility, I create an articulated arm by adding extensions as shown.

Make the primary arm from 1¼"-thick hardwood about 5" wide, tapering out to 1½" at the end. Mine is 26" long, but suit yourself. Drill a ⅜"-diameter hole through the wide end on the drill press, using a long bit. Bore as deep as your drill press allows, and then raise the table to complete the hole. Rout or sand a bullnose onto the wide end. You can drill a hole on the narrow end to carry a lamp, or add



an extension or two. Make an extension 1¼" thick by 1½" wide, and attach it to its mating arm with a ⅜" carriage bolt, a washer, a lock washer, and a nylon nut or a pair of nuts jammed against each other. Tighten the hardware enough to provide both friction and adjustability. Mount two metal L-brackets to the primary arm, using a length of ⅜" threaded rod secured at each end with a pair of jam nuts, and then screw the brackets to a wall stud.

—Mike Kehs, Quakertown, Pennsylvania



ENGRAVE IT. CUT IT. MARK IT.

The finishing touches start here.

Creating your own custom cabinet and wood finishing designs has never been so easy. Epilog's versatile laser systems allow you to etch and engrave intricate designs and inlays in a matter of minutes.



3D Engraving



Inlays




Photo Engraving



Desktop systems starting at \$7,995

To request a brochure, DVD, and samples, contact us at:


epiloglaser.com/woodcraft • sales@epiloglaser.com • 888-437-4564

MADEINUSA
Golden, Colorado

Crosscutting short multiples

Awhile ago, I was making wooden tabletop clips and needed to crosscut multiple short pieces to identical lengths. Marking individual cutlines would have taken too much time, so I decided to set up a stopblock on my power mitersaw. Unfortunately, at the end of the cut, the saw would jettison (and often ruin) the freed piece, which had been trapped between the blade and the stopblock.

After a bit of head scratching, I realized that the fix is to set up the cut with a removable spacer between the stopblock and the end of the workpiece. Hold the workpiece firmly against the fence and stopblock while removing the spacer. Now the sawn piece has room to fall freely away



from the blade at the end of the cut. To further minimize the chance of kickback, allow the blade to stop fully before raising it out of the cut.

—Ralph Burns, Montgomery, Alabama

The Dust Cobra® The Most Versatile Small Shop Dust Collector You Can Buy!



Certified full unit HEPA vacuum. Meets EPA RRP requirements including lead!

- ▶ 3x the power of most shop vacuums. Can be used with long hoses.
- ▶ Internal filter cleaner. No removal, no mess.
- ▶ Stationary or portable.
- ▶ ETL Certified

Now re-designed with a molded, static conductive body made from industrial resin to be lighter, more efficient and have even more CFM but with the same strength and quality that Oneida is known for. We just keep making the best even better!



Like Call Today for Information!
800.732.4065



FREE Online Catalog!
www.oneida-air.com

Pat. # 8,393,050

Perfect router-cut dados

Hardwood plywood usually doesn't match its nominal thickness; it's typically undersized between $\frac{1}{64}$ " and $\frac{1}{32}$ ". Therefore, when routing dados, a single pass with a single bit is unlikely to yield a perfect fit. (Even "undersized" panel bits sold for the purpose may not exactly suit the thickness of your particular stock.) To solve the problem, I've come up with a two-spacer trick to rout perfectly sized dados. All you need is a bit that's a smaller diameter than the desired dado width, a couple of scraps of wood, and a straightedge fence to guide your router.

First, make a spacer that's exactly the same thickness as your bit diameter. To set up the cut, sandwich the spacer between the fence and router base, and align the bit with the dado layout line that is nearest the fence. Secure the fence and rout your first pass. Next, replace the spacer with a scrap strip of your plywood stock, standing it on edge. Then make a second pass with the same bit to create a dado of perfect width.

—Ryan Reese, New York, New York

When using a $\frac{1}{2}$ " bit, make first pass with a $\frac{1}{2}$ " spacer against the fence.

Fence

$\frac{1}{2}$ " straight bit

Make second pass with scrap plywood stock against fence.



GREAT SAWMILLS. SHOCKING VALUE.




Premium band sawmills from only \$4397. Get your Free Info Kit.
info@NorwoodSawmills.com | 1-800-567-0404 EXT. 653



Rotating carver's easel

When I'm relief-carving panels, I prefer to work at an easel, which reduces the amount this old back has to bend. While working on an intricate design recently, I found myself constantly reorienting the panel to allow carving with the grain. To make the job easier, I screwed a rotating platform to the easel, attaching the carved panel to the platform by wedging it between cleats, as shown. Now I can simply rotate the platform and workpiece as necessary to gain the best angle of attack.

I find that the single pivot screw creates enough friction between the unfinished easel top and



platform to stabilize the platform. However, if I find it shifting under tool pressure, I'll drive an additional locking screw through its corner.

—Philip Houck, Boston, Massachusetts

Foreman

PROFESSIONAL-GRADE POCKET-HOLE MACHINE

NEW

TWICE the SPEED. Half the Effort.

The all-new Foreman makes Kreg Joinery™ even faster and easier. You get the features of our professional-quality machines at a consumer-friendly price, so you can create perfect pocket holes twice as fast as using a standard pocket hole jig...

Create All 3 Kreg Joint Sizes
Standard | Micro-Pocket* | HD (Heavy Duty)*
*SOLD SEPARATELY

Single-Pull Control Handle

Adjustable Fence System

Powerful 110v Built-In Motor

Quick-Change Drill Chuck

Perfect for Shop and Site Use

Large Cast-Aluminum Table

Affordable Only \$399⁹⁹

HIGH-SPEED POCKET HOLES IN 3 STEPS...

1 Place Your Workpiece

2 Pull the Handle

3 Create Perfect Pocket-Holes... Fast!

www.kregtool.com
800.447.8638

The American Woodshop

with Scott & Suzy Phillips

Season 22 -
Scott And Suzy -
Bringing It Home

Fantastic Home Accents -
Hand Skill Builders

Presented by - WBGU Public Television

WBGU Public Television presents 13 PBS TV shows of *The American Woodshop* "Scott And Suzy - Bringing It Home."

Season 22 shares woodworking tips for every skill level. Techniques include: turning, joinery, tool tune-ups, making jigs, bench building, furnituremaking and cabinetmaking! It's Tool Time!!!

wbgu.org/americanwoodshop

The American Woodshop Is Sponsored By:

Kreg Tool Company, Woodcraft Supply,
Gorilla Glue, Easy Wood Tools & O'Keeffe's Working Hands

© 2015 Sylvan Tool Works, Inc. All Rights Reserved




Best of Tips and Tricks

Perfect tongue-and-groove fits


Project plans often call for rabbeting the edges of a panel in order to create a tongue that slips into a drawer or rail groove. This is often done with a router bit or tablesaw dado head, with the work fed flat on the table. Unfortunately, done this way, any inaccuracy in the thickness of the stock is transferred to the thickness of the tongue, creating an ill fit in the groove.

One way to ensure a perfect tongue-and-groove fit is to create the rabbet by making two intersecting cuts on the tablesaw, feeding the edge to be rabbeted


1. Saw tongue to thickness with tongue between fence and blade.



against the fence. Set up the first cut to rip the tongue to thickness, feeding the panel on edge with the tongue face against the fence. Use a featherboard to ensure consistency of cut. Now set up to make the intersecting cut against



2. Complete rabbet by sawing tongue to final width.



Featherboard ensures consistent cuts.

Tunnel under auxiliary fence prevents trapped offcuts.

a thick auxiliary fence, raising it enough to create a tunnel for the freed offcut to fall away without being pinched between the blade and fence, eliminating violent ejection of the piece.

—Harvey Mickelson, Reno, Nevada



THE WOODTURNING SYSTEM™



The Easy Chuck now includes a FREE double-ended Easy Chucking Screw





Snap-Lock SLT Technology



- Turning Tools
- Parting Tools
- Hollowing Tools
- Chucks
- Accessories



• Big Easy Jaws • 1/8" Easy Parting Tool

In 12", 16", and 20" diameters.

The world's only carbide insert parting tool for woodturners.



Includes a **FREE** extra P11 Cutter with tool purchase



www.easywoodtools.com | 1-866-963-0264


Adjustable drawer-planing perch

To plane a drawer side, you typically need to hang it on a support board that's cantilevered off the edge of your bench. The problem is that the work can shift around on a board whose width doesn't exactly match the inside dimension of the drawer box, and clamps can get in the way of planing.

Instead of a single board, I use sticks because they can be wedged to apply pressure against the sides of any sized drawer to secure it without clamps. To create the setup, extend three stout sticks across your bench

as shown, with one of them resting against a projecting bench dog. With the drawer hanging on the cantilevered ends of the sticks, clamp their opposite ends to the bench, and then wedge a couple of cross sticks between them to create pressure against the sides of the box. (Note that the center cantilevered stick supplies support for full-length planing of the drawer side. If you're just cleaning up the joints at the corners, you can

omit it.) When planing, work in the direction of the bench dog.
—Philip Houck, Boston, Massachusetts





NEW Clear ChalkBoard Paint

Create a fun and functional chalkboard on almost any surface with Rust-Oleum® Clear Chalk Board Paint. Let your creative side capture your thoughts and art in a unique way.



- Apply To Metal, Wood, Masonry, Drywall, Plaster, Glass, Concrete, Unglazed Ceramics And Hardboard
- Writeable-Erasable
 - Latex Paint
 - Clear Finish
- Cleans With Soap And Water
- Indoor Use Only

Available at **WOODCRAFT** and other fine retailers nationwide.



Thin-plate ZCI

My hybrid tablesaw has a 1/8"-thick metal throat plate that sits in an opening with very shallow ledges. This shallow recess complicates making a zero-clearance insert (ZCI) for the opening in order to minimize exit tear-out and prevent narrow rippings from falling into the saw. My solution is to modify the stock throat plate.

Make a sub-plate by cutting a piece of 3/8"-thick plywood to fit between the leveling screw tabs in your table opening. Wax the underside of the stock plate and the inside edges of its slot (to resist glue when attaching the filler strip later), and then

1) Shape sub-plate to fit between leveling screw tabs in table recess.

screw the plate to the plywood with flathead screws driven through six countersunk holes you drilled through the plate. Next, thickness a hardwood blank to match the width of the slot, and then rip from the blank a strip that's just a hair wider than the thickness of the plate. Crosscut this slot-filler strip to the slot length, and then glue and clamp it to the underlying plywood, topping the strip with waxed paper and a caul. After the glue dries, sand the strip flush to the





plate. (To avoid scratching your plate, mask off the surrounding area with tape.) Alternatively, unscrew the stock plate, and hand-plane the strip, testing the fit as you work. Finally, clamp down the finished ZCI, and raise the spinning blade through it.
—David Schermock, Humble, Texas

Clamp-free portable saw guide

When it comes to shop-made guides for portable circular saws, there are two important criteria: The first is that the guide tracks the saw accurately. The second is that the edge of the guide aligns perfectly with the blade so that no offset needs to be calculated when setting up a cut. For tracking purposes, my 3/4"-thick guide includes a 3/4"-wide, 3/8"-deep slot, which guides a wooden runner that screws to my saw base. (When affixing the runner, make sure it's perfectly parallel to the blade.) I made the base oversized initially and then trimmed it to final width with the saw running

in its slot. That aligned the edge of the guide with the blade for easy positioning against a cutline. I made the track about 54" long so it generously spans a 4 × 8' sheet of plywood crosswise.

The real trick here, though, is that this guide does not require clamps to hold its position. Instead, I attached a sheet of rubber "nonslip padding" to the underside of the base, keeping it back from the edges 1/4" or so. The padding—designed to



hold workpieces in place for routing, sanding, and other maneuvers—is simply stapled in a few places along its perimeter. It holds the guide in place remarkably well with no slippage whatsoever that could compromise cut accuracy.
—Russ Svendsen, Olean, New York

WOODCRAFT®



For more information call (855) 923-7326,
visit www.woodcraftfranchise.com,
or email: WoodcraftFranchise@woodcraft.com

"When I think about owning my own business ...

When woodworking is your passion, and owning your own business is your goal, Woodcraft can help you take your skill and expertise to the retail level.

... I think of Woodcraft"

Carve a niche for yourself in woodworking with a Woodcraft retail store. It is difficult to overstate the importance of a brand name with a reputation for quality. The Woodcraft name is a tremendous asset. If you are a woodworker, you already know what we mean.

Now, after more than 80 years, the Woodcraft name is even more recognizable than at any other time in our history. Are you seriously looking for a franchise opportunity? Are you passionate about woodworking? Would you like to consider opening a store in your area?

Contact us today to find out how to open the door to your Woodcraft Retail Store!

David & Aaron Sapp
Nashville, TN Franchise Owners

"We're building a business that transcends generations. Having a Woodcraft franchise has helped us grow as a family while preparing our next generation for success."



*Open the door
to your own
business!*



F15WD01P

Woodcraft Franchise, LLC
1177 Rosemar Road, P.O. Box 245
Parkersburg, WV 26102-0245

RETAIL FRANCHISE OPPORTUNITIES™

INNOVATIONS WOODCRAFT[®] magazine AWARD

Top 10 Game-Changing Tools of the Past 10 Years

Over the last decade, the editors of *Woodcraft Magazine* have seen and reviewed a multitude of new products. Some simply represented an attempt to build a better mousetrap, but a few have made fresh impressions on the woodworking world, and we're betting that they are likely to continue making ripples for years to come.

While dozens of products deserve kudos, here, we have winnowed our list to the top 10. These items deserve special mention not only for making woodworking faster, easier, and safer, but also for their likely impact on future tool and product innovations. Even for those whose woodworking feet are firmly planted in tradition, no one can deny that these tools have broken new ground.

#1

Better woodworking "by the numbers"



Lignomat Digital Moisture Meter, \$199.99;
Wixey Digital Calipers, \$39.99; General Tools Digital
T-Bevel, \$38.99; Wixey Digital Angle Gauge, \$39.99

Woodworkers are constantly looking for ways to improve accuracy. In the past, this typically meant combining experience with various qualitative methods and maybe a few pricey tools.

Today, digital meters and gauges offer a shortcut to hair-splitting accuracy by giving woodworkers the ability to measure their work and calibrate machinery quickly and easily. Compared to earlier precision measuring tools such as Vernier gauges and calipers, digital tools are simple to use and easy to read (a blessing for older eyes). This has really helped woodworkers home in on the detail of the craft, allowing precise assessment of joint tolerances, machine setups, and even hand-tool operations. As production costs continue to drop, manufacturers are sure to develop digital upgrades for myriad other woodworking accessories and operations.

#2

A fresh spin on turning tools

When it comes to the often tricky craft of woodturning, Easy Wood Tools (EWT) wins the "Keep It Simple" award. While traditional turning tools require the user to "ride the bevel," EWT tools take a much easier approach. To use one of these innovative tools, simply hold it flat and level on the rest, advance the cutter into the workpiece, and let the shavings fly. EWT tools' carbide tips solve another obstacle: sharpening. Taking a cue from the saw blade and router bit industries, EWT outfits their tools with carbide tips. According to the manufacturer, carbide lasts up to 20 hours longer than high-speed steel. And when the edge dulls, you simply rotate the cutter or replace it with a fresh insert.



Easy Wood Turning Tools, \$59.99-\$149.99

Brand-new battery, motor, and charger technologies have allowed some manufacturers to now employ lighter-weight, lower-voltage batteries without cutting runtimes. For example, Milwaukee's 18V, 7¼" circular saw and Festool's 14.4V, TI 15 Hybrid Drill/Driver outperform many cordless tools twice their size. Their brushless motors, lithium batteries, and chargers are designed to work together, monitoring the motors and batteries in order to optimize performance and control overheating. Based on the performance of these tools, you can expect to see more heavy-duty tools—such as mitersaws and routers—"cut the cord" in the years ahead.

#3

Fully-capable cordless tools



Milwaukee M18 7¼" Cordless Circular Saw, \$329;
Festool TI 15 Hybrid Impact Drill/Driver, \$525

#4

Smaller bites = smoother cuts



Steel City Planer, \$499.99; Laguna 8" Wedgebed Jointer, \$1,945; Jet 12" Planer/Jointer, \$3,364

For those who have felt the pain that comes when perfectly-adjusted planer or jointer knives hit a hard knot or grain of sand, relief is in sight. The latest generation of planers and jointers now sports cutterheads that have dozens of machined pockets that accept small multi-sided cutters. When a cutter becomes dull or gets damaged, simply loosen a screw and turn the cutter to expose a fresh edge. No additional setup is required. Another plus: segmented cutterheads create less tear-out when machining figured woods.

In the last few years, many higher-end machines have come equipped with segmented cutterheads, and replacement cutterheads are available for older machines. Today, segmented cutterheads are starting to filter down to more affordable machinery. We're hoping that this upgrade becomes a standard option on many more machines in the near future.

#5

Mortises made simple

Mortise-and-tenon joinery ranks as one of the strongest means of attaching parts, but cutting these joints can be time-consuming and may require an elaborate setup. That changed in 2007 when Festool introduced the Domino, a handheld machine that combined the simplicity of biscuit joinery with the strength of loose-tenon joinery. The Domino DF 500 and larger XL DF 700 employ a patented oscillating cutter that plunge-cuts and then moves from side to side to create a perfect mortise as you press the tool into the work.

In terms of speed, precision, strength, and size, no other mortiser comes close. Thanks to the Domino, furniture makers can now focus on design and let the machine tackle the formerly tricky joinery.



Festool Domino DF500Q, \$850;
Festool Domino XL DF700, \$1,250



Top 10 Game-Changing Tools of the Past 10 Years

#6

Finishing and stripping without a mask

Water-based finishes have an established reputation for being less odorous and easier to use than oil-based finishes. Today, many outperform their oil-based competition. According to the manufacturers' tests, General Finishes' High Performance finish (a polyacrylic blend) is the hardest, most durable consumer polyurethane topcoat on the market. This clear finish contains a UV stabilizer that protects underlying stains from fading and prevents the cured finish from breaking down in sunlight. Enduro-Var is an oil-modified alkyd varnish in a water-based formula that dries fast and cleans up with water, yet imparts the desirable amber tone of an oil-based varnish.

On the other side of the coin, safer products also exist for removing finishes. SOY Gel removes multiple layers of paint, urethane, acrylic, epoxy, or enamel, but does not emit toxic fumes and can be cleaned up with water.



General Finishes High Performance Polyurethane, **\$25.99/qt.**;
General Finishes Enduro-Var, **\$29.99/qt.**;
SOY Gel Professional Paint Stripper, **\$20.99/qt.**

#7

Solid, stone-simple joinery



Kreg Foreman, **\$399**; Kreg R3, **\$39.99**

Modern pocket-hole joinery was born in the latter half of the 1900s, and has proven to be an easy, affordable, and effective method of fastening cases, face frames, and other parts without having to wait for glue to dry. Recent developments by manufacturers have made the job even easier. The wide variety of jigs and accessories now available enables production shops and DIYers to select the tools they need to tackle ever larger projects, such as cabinets, and furniture, without an arsenal of clamps, complicated setups, or heavy machinery.

A decade ago, CNC (computer numerical control) machines existed almost exclusively in commercial shops. Today, affordable tabletop models have sparked purchases by a significant percentage of small-shop woodworkers as a complement to their array of shop machines and hand tools. Many beginners are adopting CNCs because the machines enable them to rout precise inlays, cut out perfectly fitting project parts, and take on projects they previously avoided because they lacked the skills or tools.

CNC machines require a learning curve, but that may not be such an impediment in an age where many of us can set up a computer faster than we can fettle a plane. CNC-inspired technology is already appearing on other machines, including mitersaw stations and router table lifts and fences.

#8

Plug-and-play woodworking



General iCarver 915X, \$4,699.99

#9

Motors with brawn AND brains



Teknatool Nova DVR XP Lathe, \$2,399

A Digital Variable Resistance (DVR) motor is a direct-drive motor that relies on electromagnets instead of brushes. A micro-computer controls spindle speed and torque by switching these magnets on and off, eliminating the need for belts or pulleys. With the Nova lathe, the DVR motor constantly senses load and adjusts torque to maintain your desired RPM, even at super-low speeds. In addition to speed control and higher torque, a DVR's use of magnets instead of rotors and brushes means that there are fewer parts to wear out.

In the next year, Teknatool plans to launch a DVR drill press that can slow a bit as it exits the back of your workpiece to reduce tear-out, and even shut down the unit if it senses that you've accidentally left your chuck key in the chuck. You can bet you'll see this technology in tablesaws and other critical machines in the future.

#10

Finger-saving saws



SawStop Tablesaws (several models available). Prices range from \$1,599 to \$2,729.

Unlike most woodworkers, Steve Gass refused to accept the notion that working at the tablesaw must be dangerous. In 2004, Gass introduced the world to SawStop's flesh-detecting technology, and proved that it is possible to be faster than a spinning saw blade. In 1/200th of a second, the sensor detects fleshy contact and then triggers the brake to stop and drop the blade—often leaving the would-be victim with barely a scratch. Since their inauguration, SawStop tablesaws have saved thousands of digits. Aside from the safety advantage, SawStop's standard features rank it as one off the best tablesaws in today's market.

(Fun factoid: The company performs its now-famous "hotdog demonstration" almost 1,000 times each year.)

WOODCRAFT[®] magazine



GRAND PRIZE

Morris Chair and Ottoman
from the Oct/Nov 13 and
Feb/Mar 14 *Woodcraft*
Magazine issues!
Over **\$6,500** value.

\$10,000 BLOCKBUSTER SWEEPSTAKES

ENTER AT
WOODCRAFT.COM/10KSWEEPS

ENTER FOR A CHANCE TO **WIN**
AS WE CELEBRATE OUR **10TH ANNIVERSARY ISSUE!**
Nov. 1, 2014 – JAN. 31, 2015

SECOND PRIZE

NEW!

JET 14" Lathe
(model #719400K)
\$1,600 value +
Easy Wood Tools
Mid-Size bundle
\$360 value



THIRD PRIZE

RIKON 18"
bandsaw
(Model #10-341)
\$1,300 value



SPONSORED BY

WOODCRAFT[®] magazine



FOURTH PRIZE: 10 people
will receive the 1st 5 Years of
Woodcraft Magazine CDs

FIFTH PRIZE: 5 people will
receive 1-year *Woodcraft*
Magazine subscriptions

TO ENTER: Stop by your local Woodcraft store, or visit
us online at **Woodcraft.com/10kSweeps**

For complete rules, visit Woodcraft.com/10kSweeps

No purchase necessary. One entry per person, household, and
email address. Void where prohibited.



CONSISTENT. **QUALITY.** PERFORMANCE. **THE TOOLS YOU'VE** BEEN WAITING FOR.

At **Armor Tool**, we understand very well the Craftsman's thirst for innovation and a better way to get the job done. Well, we're going to get along just fine. Armor Tool is our new company, but we are not so new after all. For over 30 years, our team has provided profound Tool innovations marketed through some of the world's best known brands. Our newest innovation is our patented Auto-Adjust Technology. Armor's introductory line of **Auto-PRO™** Toggle Clamps and our Peg Table Clamping system, feature Auto-Adjust technology, but also deliver it in a versatile system that is as innovative as the technology itself.

Anyone who has ever used a toggle clamp understands that constant pressure adjustments are the norm. Armor's technology has changed that. **Auto-PRO™** Toggle Clamps automatically apply consistent clamping force over a range of material thicknesses. You set the clamping pressure once, and change the material as often as you like. Our new **Auto-PRO™** Peg Table Clamping System delivers our Auto-Adjust technology in multiple dimensions. Our Horizontal Peg Clamp delivers Auto Adjust clamping anywhere on a table, spins 360 degrees or even raises above the table up to 7 inches. All of this capability delivered in seconds - without adjustment. With innovation as our continuous goal we are only getting started. Take a deeper dive into Armor Tool. Check us out at: www.ARMOR-Tool.com



SMART TOOLS. SEAMLESS WORKFLOW.

Votive Candle Stands

Make this matching set of Arts & Crafts home accents.

By Marlen Kemmet



(large) $4\frac{1}{2}"w \times 4\frac{1}{2}"d \times 9\frac{3}{4}"h$

(small) $4\frac{1}{2}"w \times 4\frac{1}{2}"d \times 7\frac{1}{4}"h$

(medium) $4\frac{1}{2}"w \times 4\frac{1}{2}"d \times 8\frac{1}{2}"h$

Hone your tablesaw skills crafting a trio of stands in three heights. I used frame-and-panel construction to build them and a jig to taper-cut the uprights. For a consistent grain pattern, I chose riftsawn white oak for the uprights and quartersawn white oak for the panels.

Note: To make this trio of stands, adjust the length of the uprights and panels. See the **Cut List** for dimensions. By lengthening parts (A) and (D), you can make three different stand heights. See the **Convenience-Plus Buying Guide** for the square, frosted votives seen here.

Start with the Uprights

1 For the uprights (A) for all three stand sizes, cut four blanks for each stand to $1\frac{1}{4}"$ square by the lengths in the **Cut List**. I laminated thinner stock to create the $1\frac{1}{4}"$ -square upright blanks. (To do this, I initially cut 8 pieces a few inches longer than needed.)

Tip Alert

Consider cutting a few extra blanks for verifying your cuts in the following steps.

2 Fit your tablesaw with a dado blade and featherboard. Then cut a pair of $\frac{1}{4}"$ grooves $\frac{1}{4}"$ deep along two inside edges of each upright (A). Mark the taper cutlines on the outside faces of each upright for reference in the next step.

3 Build the taper jig shown in **Figure 2**, and fit your tablesaw with a zero-clearance auxiliary saw top, adhering it with double-faced tape. (I used $\frac{1}{8}"$ hardboard.) Since you are trimming narrow pieces off two edges of each upright, the auxiliary table prevents the off-cuts from falling into the blade

Figure 1: Candle Stand Exploded View





Figure 2: Taper Jig




and shooting back. To push the jig and upright through the cut, use a pushblock and use the tape to adhere the workpiece to the taper jig. Make the first taper cut on each upright as

shown in **Photo A**. Rotate the upright on the jig 90°, and make the second taper cut. (The taper cuts are opposite the edges having grooves.)



Adjust the fence so the blade aligns with the marked cutline, and make the first tapered cut.



B When crosscutting the short rails, a notched hold-down stop is needed to secure the pieces.



C Use a sharp dado blade and backer board to create near perfect notches without chipping.


Create the frames

1 Cut the top rails (B) and the bottom rails (C) to the sizes in the **Cut List**. Fit your tablesaw with a dado blade, and cut a pair of opposing rabbets across each end of the rails so the resulting tenons fit snugly within the $\frac{1}{4}$ " grooves in the uprights (A). For safety when cutting the rabbets, I used a miter gauge fitted with an auxiliary fence and hold-down stop, as shown in **Photo B**. When crosscutting short pieces, push the stock and miter gauge across the dado blade. Turn off the saw, reposition the miter gauge and workpiece, start the saw, and cut the next rabbet. Pull back the miter gauge after the blade stops.

2 From $\frac{1}{4}$ "-thick solid white oak stock, cut four panels (D) to size for each stand plus $\frac{1}{4}$ " in width using a standard $\frac{1}{8}$ " blade. Make two ripcuts through each panel blank, where dimensioned in **Figure 3**. Fit your tablesaw with a $\frac{1}{4}$ " dado blade and cut four $\frac{1}{4}$ " notches in each edge of the four center strips, as shown in **Photo C**.

3 With the surfaces and ends flush, glue and clamp the panels back together. Clamp the pieces

Figure 3: Panel-Cutting Sequence




Note: Finished width of panel is $2\frac{1}{2}$ "

making up the panels on a length of particleboard or plywood that is covered with waxed paper, as shown in **Photo D**. Use finish nails along the edges of the panels to hold the pieces together until the glue dries. (You don't need a lot of clamping pressure here. Plus, the parts are easy to adjust.) Later, remove the nails, and sand the panel surfaces smooth.

4 Sand all the pieces (A, B, C, and D) smooth. Dry-assemble two frames in the configuration shown in **Photo E** to check the fit of the rails and panels between the uprights (A). Now, glue and clamp the frames together. Add the remaining panels and rails to form the stand assemblies.

5 Rip a long $\frac{1}{4} \times \frac{1}{4}$ " filler strip (E) to fit within the exposed groove in each upright below the bottom rails. Crosscut the filler strips to length, and glue them in place. If necessary, sand the bottom ends of the strips flush with the bottom ends of the uprights (A).





Tap in nails in the particleboard to snug up and edge-join several panels at once; the particleboard provides a flat surface on which to work.



Check for a flush fit at the assembly's top end before gluing the parts together.

Figure 4: Top Blank-Cutting Sequence





Employ a pair of corner cleats attached to a sheet good substrate to make clamping up the mitered top easier to manage.

Votive Candle Stand (materials for one stand)

	Part	Thickness	Width	Length	Qty.	Mat'l
A1*	Uprights	1¼"	1¼"	9¼"	4	RSWO
A2*	Uprights	1¼"	1¼"	8"	4	RSWO
A3*	Uprights	1¼"	1¼"	6¾"	4	RSWO
B	Top rails	½"	1"	2½"	4	RSWO
C	Bottom rails	½"	1¼"	2½"	4	RSWO
D1*	Panels	¼"	2½"	6½"	4	QSWO
D2*	Panels	¼"	2½"	5¼"	4	QSWO
D3*	Panels	¼"	2½"	4"	4	QSWO
E*	Fillers	¼"	¼"	½"	8	RSWO
F*	Top pieces	½"	1½"	5⅛"	4	RSWO
G	Top panel	¼"	2⅝"	2⅝"	1	RSWO

*Indicates parts that are initially cut oversized. See instructions.

A1 and D1 are used for the 9¼"-tall stand, A2 and D2 for the 8½"-tall stand, and A3 and D3 for the 7¼"-tall stand.

Materials: RSWO = Riftsawn Oak, QSWO = Quartersawn Oak

Convenience-PLUS BUYING GUIDE

<input type="checkbox"/> 1.	Freud SD208 Pro Circular Saw Pro Dado Saw Blade Set 8" x ⅝" bore	#127245	\$99.97
<input type="checkbox"/> 2.	General Finishes Water-Based Stain, Black Cherry, 1 pt.	#818820	\$11.49
<input type="checkbox"/> 3.	Watco Lacquer Gloss Spray, 11.25 oz.	#146946	\$9.99
Above items are available at Woodcraft stores, woodcraft.com or by calling (800) 225-1153. Prices subject to change without notice.			
<input type="checkbox"/> 3.	Eastland Square Tealight Frosted Candle Holders, Set of 12. Size: 2"(H) x 2"(W); candles sold separately.	1151_12_TL	\$12.99
Above item is available at http://www.quickcandles.com , or by calling (800) 928-6175. Prices subject to change without notice.			

Make the top assembly

1 To form the top (F), cut a piece of ½"-thick oak to 1⅝" wide by 25" long, as shown in **Figure 4**. Along one edge, cut a ¼" rabbet ¼" deep to fit the top panel (G) later. Bevel the opposite edge at 30° on your tablesaw for a finished width of 1½".

2 Next, using a stop, miter-cut four 5⅛" long pieces from the strip, and glue them together as shown in **Photo F**. Later, sand the top smooth and lightly sand along the outside chamfered edges to soften them.

3 Cut the top panel (G) to size, and glue it into the rabbeted bottom in the top (F).

Glue the top to the base, and finish

1 Finish-sand the top and base assemblies through 220 grit.

2 Center and glue the top assembly (F/G) to the base assembly. Remove any squeeze-out, and let the glue dry.

3 Stain the votive candle stand. (I used General Finishes Black Cherry thinned 30% with water.) Finally, apply a clear finish. (I used spray lacquer.) ■

About Our Author

A founding member of the San Diego Woodworking Association, Marlen Kemmet's career in woodworking and woodworking publications stems back to the early 1980s. He likes building furniture and home accents in the Greene-and-Greene style for his home in rural Dallas County, Iowa.



10 Essential Sharpening Tricks

Hone your sharpening skills ... and your tools.

By Andy Rae

Sharpening straight-edged tools, such as chisels and plane irons, is a necessary and regular part of ownership. A dull tool is a dangerous tool. A sharp tool cuts better and is safer because you have more control, and the results speak for themselves: You get clean, flat surfaces that are free of scratches, crisp lines that hit the mark without chipping or blowing out, and the joy of pushing or pulling a tool without

undue force or stress. In short, a sharp tool is a good tool. Anything less, and it's time to sharpen.

To keep your sharpening regimen accurate, effective and fast (so you can get back to working wood) I've outlined ten tactics for better edges. These sharpening methods are organized into three core categories: grinding, honing and polishing. While I use waterstones for the lion's share

of my sharpening, most of the tips shown here can be used with other sharpening tools, such as oilstones, ceramic stones, diamond stones, or even—if you're so inclined—sandpaper. Implementing these strategies into your regular sharpening regimen is bound to boost your sharpening skills so you can get back in the game in short order, with edges super sharp for the most demanding tasks.

Grinding Tips

1 Set up your grinder for success

Shaping new tools, altering bevel angles, or simply removing nicks in an edge are all part of a bench grinder's job. But not all grinders are created equal. Spinning at 1,750 rpm, a slow-speed grinder generates less heat than a conventional 3,450-rpm grinder, making it less likely to burn, or "blue," your tools. Listed by the diameter of their wheels, you can choose from 6" or 8" models. Larger wheels grind more steel in less time, but will heat edges more readily; smaller models typically cost less.


For optimum control, position the grinder high, so that the center of its wheels sits at about the height of your bent elbows (typically 44" to 48" from the floor). This setup lets you lock elbows and use your upper body and forearms for smoother tool movement side to side. Of course, a sturdy tool rest is essential. Look for a large table that's easy to fine-tune for height and angle, and one that locks securely. A tool rest that's notched to surround the wheel is a handy feature for light side grinding.

For most woodworking tools, a 120-grit wheel is the best choice. Look for wheels with a vitrified bond. These break down easily in use to expose fresh particles, reducing heat buildup and lessening the chance of bluing. Because wheels wear and collect metal debris, you'll need to dress the working surface periodically. I use two dressers to keep my wheels clean and to shape



Use a dressing stick to clean and shape the wheel, making a slight belly in the middle by forming a gentle arc, cutting back the sides about $\frac{1}{4}$ " (inset).

A Hollow-Ground Edge Is Easier To Hone



them. The first is a diamond dresser that cuts very fast and lets you remove deep grooves and imbedded metal particles. I follow this with a silicon carbide dressing stick to smooth the surface and refine the shape into a slight belly. The belly prevents over-grinding and provides more control, especially with narrow tools. And since you're cutting in the center, you don't have to

sweep a wide tool completely off to the side of the wheel as you would with a flat wheel.

With the right grinder setup, you'll automatically grind a slight concavity into the bevels of your chisels and plane irons. This "hollow-grind" (which matches your wheel diameter) has the benefit of making the tool much easier to hone by hand, as I'll describe on page 38.

2 Reshape an edge to square

A square edge is the goal when grinding most edge tools. The tricky part is marking out an accurate reference line to work to when grinding, since steel resists pen and pencil. The fix is to spray a coat of fast-setting layout fluid, or *machinists' bluing*, on the back of the chisel or iron up to the cutting edge. Use a small square and a sharp awl or other fine-pointed tool to etch through the thin, uniform color close to the edge, exposing a precise line that's square across the face of the back. You can grind to the line, or simply use it as a mark for eyeballing straight and square. The thin paint comes right off with a swipe of denatured alcohol, or with two or three passes over your stone.



Spray the back of the tool with layout fluid, let it dry, and then scribe a clean line square to the sides and near the cutting edge.

3 Color the bevel to gauge the grind



Color the bevel, and then grind it by keeping the tool moving sideways. You're done when all the color is gone.

A consistently ground bevel is key to a well-sharpened tool. But it can be tricky to reliably assess your progress during grinding. A dark felt marker can take the guesswork out of the job, letting you gauge your progress as you grind. Mark the entire face of the bevel, and grind until all the color is removed.

Once you get the knack for grinding a smooth, consistent bevel, take a close look at your work. A pocket magnifier or a photographer's loupe will help you see the very cutting edge, and whether it's even and without large chips, or whether you need to go back to the wheel.

4 Put the heat in the sink



Upcycle a heat-sink from an old computer, and press the back of the tool on it to dissipate heat. Double-faced tape holds the sink to a piece of plywood, letting you cool your tool where you grind.

Quenching a hot blade in water is a recipe for disaster. Too hot, and the plunge can create tiny fractures in the steel, weakening the edge. Instead, you can cool off

a hot blade without stressing the steel by holding it on a computer heat-sink for a few moments. They're typically free from any neighborhood computer whiz kid.

Honing Tips


1 Prep and hold your stones

For good control, set up your honing station relatively low, or about 30"-36" from the floor to the top of the stone. I use a series of waterstones for honing and polishing. For rough work, where the edge is badly deteriorated, start with an 800-grit stone. But for most sharpening, begin with a 1200-grit stone for honing, and then move directly to a 6000- or 8000-grit stone for polishing.

Mark the grit on your stones by labeling their ends (not their sides) with a hard, pointed object such as a carbide-tipped pen. If you use an awl instead, be prepared to resharpen it afterward.


To prevent chipping, slightly chamfer all the sharp edges on both new and worn stones by rubbing them with a 150-grit sanding block or a flattening stone (see illustration at right). Pay particular attention to the ends, where chipping is most likely, making the chamfers wider here.

A simple plywood tray will hold stones securely and can be conveniently dogged to your benchtop. Keep a spray bottle of water on hand to wet the stones as you work. When honing either the back or the bevel, I resist conventional wisdom by positioning the tool sideways on the stone and then moving it forward and backward. I find that this approach provides more control and allows greater tactile feedback while allowing me to maintain the tool at a consistent angle.



A shop-made tray holds coarse and fine stones for honing. Stones are wedged securely between tapered sticks (inset).

Honing Tray



2 Keep your stones flat




Use plenty of water, and push the flattening stone as you would a plane, with even pressure

front and back. Deep grooves trap waste and speed up the flattening process (inset).

Flat stones make for precise sharpening, so it's important to true your waterstones on a regular basis. You can use any stone to flatten another, but commercial flattening stones and diamond stones are much faster-cutting. A coarse (220-grit equivalent) diamond stone cuts faster than a flattening stone and leaves a slightly smoother surface, but it typically costs three times as much. Using plenty of water, rub the flattening stone back and forth on your honing stone, pushing straight ahead and occasionally skewing it at an angle. Once or twice, turn the honing stone 180° and repeat. It's flat when it's an even color, with no dark or light spots.

3 Hone the back flat—fast



The backs of new chisels and plane irons need flattening, and regular sharpening sometimes requires a similar amount of work. To speed up what is often a laborious process, make a $1\frac{3}{4} \times 4 \times 7\frac{1}{2}$ " hardwood block and firmly press it 1"-2" over the leading edge as you push both tool and block over the stone. Rub until the back has an even luster.



A rubbing block, sawn to fit your hand, speeds up flattening backs. Bandsaw a series of $\frac{1}{16}$ "-deep grooves spaced every $\frac{1}{8}$ " across the bottom, and wet the bottom for increased grip (inset).

4 Hand-hone the bevel

A consistent angle is paramount when honing the bevel. And thanks to the hollow-ground bevel left by the grinding wheel, honing by hand is well within the skill set of the novice. Place the bevel on the stone, and rock it slightly until you feel it firmly seated. Grip the tool with one to three fingers on the back (depending on how wide it is) and, similar to grinding, lock your elbows and move the tool with your upper body, not your arms. Your other hand simply supports the weight and helps move the tool back and forth.


Once you feel a full-length burr, flip the tool over and hone the back. For a longer-lasting, tougher edge, consolidate and refine the already sharp edge by flipping the tool repeatedly, decreasing the pressure each time until you finish with a light touch on each side.



On a wide iron, position two or three fingers close to the cutting edge, and push down hard. Rub the blade slightly past the stone's ends to prevent dishing the stone.

Polishing Tips

1 Look in the mirror



Look for a mirror polish on the bevel and the back for the toughest, longest-lasting edge.

Under a microscope, metal that's polished to a mirror-shine still reveals scratches similar to those found on a surface with a dull, or matte, finish. Although both are sufficiently sharp to cut wood, a polished surface is tougher and more durable because the edge has shallower scratches.

As you did with the 1200-grit stone, use a 6000 or 8000 stone and hone the back and the bevel, flipping back and forth to remove the burr, while decreasing pressure with each flip. If you're polishing a freshly-ground bevel, it takes only seconds to create a tiny, polished strip of metal at both the toe and heel of the bevel. The back, however, takes more work, and it's often prudent to get out your rubbing block again to initiate a shine. As before, you only need to focus on the endmost 1"-2" of the blade when polishing the back. Finish by hand, again with light pressure. It's a good exercise to inspect the surface under magnification. The goal is to rub until you can see your reflection.

2 Dub the corners

When you need to plane a wide surface, rounding over the corners of your plane irons will reduce track marks on your work. The approach is simple, but care should be taken not to groove your stone. Using a 6000 or 8000 stone, hold the iron at roughly 45° to the surface and drag the tool back towards you. On the first pass, *almost* lift the blade as you pull, then make two or three more passes with just the weight of the blade on the stone. ■



You can prevent plane track marks on your work by rounding over, or *dubbing*, the corners of your plane iron, cocking the blade at an angle, and taking three or four light passes over your finishing stone.

About Our Designer/Builder

Andy Rae is an award-winning furnituremaker whose career spans several decades. He has authored a number of books on woodworking, including *The Complete Illustrated Guide to Furniture and Cabinet Construction* (Taunton Press). He currently makes his home in the mountains of western North Carolina.

Convenience-PLUS BUYING GUIDE

<input type="checkbox"/> 1.	Rikon 8" Slow Speed Grinder	#158512	\$139.99
<input type="checkbox"/> 2.	Aluminum Oxide 8" x 1" Grinding Wheel, White, 120 Grit	#01W47	\$36.99
<input type="checkbox"/> 3.	Veritas Grinder Tool Rest	#153365	\$57.99
<input type="checkbox"/> 4.	Diamond Dressing Tool, 120 grit	#158523	\$17.99
<input type="checkbox"/> 5.	Dressing Stick	#11N51	\$17.50
<input type="checkbox"/> 6.	P704 Pocket Magnifier 4x	#154620	\$7.99
<input type="checkbox"/> 7.	King Brand Deluxe Waterstone, 800 Grit	#11H31	\$30.50
<input type="checkbox"/> 8.	King Deluxe Waterstone, 1200 Grit	#11H11	\$31.50
<input type="checkbox"/> 9.	King Ice Bear Waterstone, 8000 Grit	#149291	\$73.99
<input type="checkbox"/> 10.	Norton Flattening Stone	#833914	\$34.99
<input type="checkbox"/> 11.	DMT Duosharp 8" Diamond Stone, Coarse/Extra Coarse	#140966	\$102.99
Above items are available at Woodcraft stores, woodcraft.com or by calling (800) 225-1153. Prices subject to change without notice.			
<input type="checkbox"/> 12.	Layout Fluid, Spray		\$11.96
Above item available at McMaster-Carr, www.mcmaster.com .			

Hand Plane Cabinet

A fitting home for fine tools

By Geoff Noden

Designed By Craig Bentzley




Photos: Paul Anthony

There's a long-standing tradition of cabinetmakers displaying their woodworking skills in the form of finely crafted tool cabinets and chests. Very often, the contents include a number of hand planes, which can accumulate surprisingly quickly. It's not unusual for a serious woodworker to have a dozen or more of these tools, all of which deserve care and protection.


To that end, this dedicated hand plane cabinet was designed for beauty, utility, and accessibility. The cabinet is deep enough to compactly accommodate block and smoothing planes on the gallery shelf. This shelf is raised to the level of the top edge of the lower door rail for clear visibility and quick inventory when you're looking for a particular plane for a job at hand. The cutaway in the shelf above the gallery also aids visibility.

The upper ramps provide a good solution for storing long-bodied planes in a shallow cabinet, while perfectly presenting the totes for easy grasping. As an added benefit, the hinged ramps can be lifted upward to allow access to the interior space for storage of infrequently used items. Finally, two drawers offer compartments for plane-tuning tools, paraffin, and other related supplies and accessories.

Figure 1: Hand Plane Cabinet Exploded View



Molding Detail (Full-Sized)



Online Extra

For a sheet cutting diagram, go to woodcraftmagazine.com and click on "Online Extras."



A

For efficiency and joint accuracy, saw the dados in a “double-wide” panel before ripping it into two to create the case sides.



B

Glue a wide piece of solid wood between the plane gallery shelf and cutaway shelf. Afterward, rip through it to create two edged shelves.

Make the plywood case

1 Cut a single $26\frac{1}{4} \times 47$ " hardwood plywood panel from which you'll ultimately make both case sides (A), as shown in **Figure 2**. Make sure the panel is square, and that you've removed any factory edges.


2 Referring to the **Cut List**, saw three of the five horizontal panels (B) and the drawer divider (C) to final size. For the remaining two horizontal panels, cut a single 24"-wide \times 25"-long panel for now. You'll rip this “double-wide” panel into the two finished panels after cutting the dados for the drawer divider.

3 Referring to the spacing shown in **Figure 2**, use a dado head to saw the $\frac{3}{4} \times \frac{1}{4}$ "-deep dados in the sides (A) panel (**Photo A**).

4 Saw the $\frac{3}{4} \times \frac{1}{4}$ "-deep dados for the drawer divider (C) midway across the 25" length of the double-wide horizontal panel you cut in **Step 2**.

5 Saw the $1\frac{1}{8} \times \frac{1}{4}$ "-deep rabbets in the outermost edges of the double-wide sides (A) panel, where shown in **Figure 2**. Clamp or tape a wooden sacrificial facing to your rip fence to prevent scarring it.

Figure 2: Making the Case Sides





Use a scrap panel to square the horizontal panels to the drawer divider during glue-up, and use a carefully squared spacer panel to accurately locate the drawer guides.

6 Rip each side (A) to its final $12\frac{7}{8}$ " width. Also rip the double-wide horizontal panel into two $11\frac{3}{4}$ "-wide pieces.

7 To efficiently make the edging (D) for the horizontal panels (B) that will become the plane gallery shelf and cutaway shelf, first dress a piece of solid oak to $1\frac{3}{16} \times 3\frac{7}{8} \times 25$ ". Then edge-glue it between two of the slightly oversized horizontal panels (B), as shown in **Photo B**. After the glue cures, hand-plane and/or sand the faces of the edging flush to the faces of the panel. Then rip through the solid wood section to create one panel with $3\frac{1}{2}$ "-wide edging (for the upper cutaway shelf) and the

other with $\frac{1}{4}$ "-wide edging (for the lower gallery shelf). Clean up any saw marks, and then rip each panel to its final $11\frac{3}{4}$ " width.

8 Referring to **Figure 1**, lay out the cutaway on the $3\frac{1}{2}$ "-wide edging. Use a jigsaw or bandsaw to cut the shape, and then smooth the edge.

Tip Alert

Before assembling a cabinet like this with small, deep compartments, consider prefinishing the interior faces before assembly, avoiding any joints.

Glue up the case

1 In preparation for assembling the case, make eight thick, straight cauls, squarely crosscutting their ends.

2 Glue the drawer divider (C) into its dados (**Photo C**). Also, make the drawer guides (F), and glue them in place to the case bottom (B) at the same time, using $10\frac{1}{4}$ "-long spacer panels to aid location.

3 Dry-clamp the case together to check the fit of the joints and to rehearse your clamping procedures (**Photos D and E**). With the unit clamped up, measure for a perfect fit of the back (E), and then cut it to size. Make sure it's dead square, as it will serve to square up the case during assembly.

4 After the divider (C) joints have cured, glue up the case.

Make and fit the ramps

1 Cut the ramp panels (G) to the size in the **Cut List**. Then saw the $\frac{1}{4} \times \frac{1}{8}$ "-deep grooves, as shown in **Figure 3**. I spaced them about 3" apart, which accommodates most planes, but double-check the widths of your specific tools (for a #8 plane, allow an extra $\frac{3}{16}$ "), and adjust the spacings to suit.




Rehearse the rest of the case glue-up by first clamping across the face, with the case resting on cauls overhanging the edge of the bench.



Next, lay the case on its front, insert the back panel, and check to make sure that all the joints mate tightly.

Figure 3: Ramp



When planning your plane arrangement, keep in mind that the ramps are designed to accommodate longer planes (numbers 5, 5½, 6, 7, and 8). Smaller bench planes (numbers 4½ and under) should be placed either in the plane gallery below, or on the upper sections of the ramps. Otherwise, when placed low on the ramps, their totes may prevent the door from closing.



With the ramps centered in the case and held back ½" from the front edge of the cutaway shelf, mark along the hinges' barrels and ends to establish the hinge locations.

2 Saw the ramp edging strips (H), vertical divider strips (I), and rails (J) to the sizes in the **Cut List**.

3 Cut the biscuit slots in the bottom edges of the ramp panels (G) and in the mating edges of the ramp rails (J). Now glue and tack the strips (H, I) to the ramps, and clamp and glue the rails (J) to the ramps. Lastly, saw a 74° bevel on the top and bottom edge of each assembled ramp, where shown in **Figure 3**. For safe sawing, this is best done using a crosscut sled or a miter gauge outfitted with a long auxiliary fence.

4 Temporarily attach a 10"-long

section of continuous hinge to the rear face of each ramp at its top edge, using just a few screws for now, but drilling all of the pilot holes. (*Note that the ½"-long screws that come with the hinge will poke through the panel unless shortened. After drilling the pilot holes, I pre-threaded them by driving a screw partially in, and then removing it. I then ground about ⅛" off the tips of the screws before final installation.*)

5 Put the ramps in place, with their lower edges set ½" back from the inner edge of the cutaway shelf. Now mark the hinge locations by tracing along the hinge barrel and the ends

of the hinge leaves (**Photo F**).

6 Trace along the rear edges of the horizontal panels (B) onto the back (E). Then remove the back, extend the horizontal panel centerlines across its rear face, and drill countersunk clearance holes for attaching it.

7 Detach the hinges from the ramps (G), and screw them to the back (E), again with just a few screws, but drilling all the pilot holes. (As you did for the ramp attachment, grind about ⅛" off the tips of the screws.)

8 Glue and screw the back (E) in place with #6 × 1½" screws placed approximately 6" apart.



G

Drill pocket screw holes in the ends of the face frame rails for their attachment to the stiles.

Make the face frame

1 Cut the face frame stiles (K) and rails (L) to the thicknesses and lengths shown in the **Cut List**, but make them about $\frac{1}{32}$ " oversized in width for now. Also make the piece for the drawer box edging (M).

2 Join the stiles and rails using pocket screws (**Photo G**).

3 Glue and clamp the assembled face frame to the case.

4 Cut the drawer box

edging (M) to length, and glue and clamp it in place.

5 Use a flush-trim bit to rout the face frame (K, L) and edging (M) flush to the case.

Make the door

1 Cut the door stiles (N) and rails (O, P) to the sizes shown in the **Cut List**. For aesthetics and stability, use straight grained stock.

2 Lay out the mortises where shown in **Figure 1**, and then cut them. I used a hollow chisel mortiser (**Photo H**), but you could rout them instead.

3 Lay out the tenons where shown in **Figure 1**, and then cut them. I used a dado head on the tablesaw to do the job (**Photo I**).

4 Assemble the door, ensuring that it's dead-square under clamp pressure.

5 Rout the $\frac{1}{4} \times \frac{3}{8}$ "-deep rabbet

for the glass, and then square the corners with a chisel. Measure the distance between opposing rabbet shoulders, and subtract $\frac{1}{16}$ " in each direction. Then order a sheet of $\frac{1}{8}$ "-thick (double-strength) glass cut to that size.

6 Make the door stop strip (Q), and glue or tack it in place, flush with the front edge of the top horizontal panel (B), where shown in **Figure 1**.

7 With the case on its back, lay the door in place with a $\frac{1}{16}$ " gap between the door hinge stile (N) and the face frame stile (K). Attach the hinges, and then mark the perimeter of the door for a consistent gap all around. Remove the door, and joint or plane the edges to your lines.

Make the drawers

1 Cut the drawer box sides (R), fronts and backs (S), and bottoms (T) to the sizes shown in the **Cut List**.

2 Set up a good quality dado head for a $\frac{1}{4}$ "-wide cut. Stand a piece of drawer stock on edge against the fence and position the fence so that the face of the plywood is flush with the opposite face of the saw teeth.

Tip Alert

To prevent tear-out, begin routing the rabbet for the glass by moving the router counter-clockwise while holding it firmly. Finish up with a clockwise cut.



H


Cut the end mortises first, and then remove the waste between them with subsequent cuts.



I

For efficient sawing of tenons, register the stock against the rip fence for the first cut, and then remove the rest of the waste in subsequent passes.

Figure 4: Drawer



Raise the blade for a precise $\frac{1}{4}$ "-deep cut, and leave it at that height for the following steps.

3 Saw the dados in the drawer sides (R), as shown in **Photo J**. Use the same setup to cut the drawer bottom grooves on the inside faces of the drawer sides (R), and fronts and backs (S).

4 Reposition the fence if necessary until test cuts yield a rabbet with a tongue that fits snugly into the dados you cut in **Step 2**. Then saw the rabbets on the drawer fronts and backs by standing the stock on end (**Photo K**).

5 Reposition the fence about $\frac{1}{64}$ " closer to the blade, and cut the rabbets on all four edges of each drawer bottom, as shown in **Photo L**. (The slight fence adjustment will allow the drawer bottoms to slide easily in their grooves for simpler assembly.)

6 Glue up the drawers on a flat surface, ensuring that they're square under clamp pressure.

7 After the glue cures, check the fit of each box in its opening, and plane or sand the parts if necessary to create a nice sliding fit with no side-to-side wobble.

Attach the applied drawer fronts


1 Make the applied drawer fronts (U). The sizes shown in the **Cut List** are theoretically perfect, but it's best to gauge yours from your actual drawer openings. Match the length of each front to the width of its opening, but make it $\frac{1}{16}$ " less than the height. Cut the fronts side by side from the same board to create a visually pleasing continuous grain pattern across both faces.

2 At the drill press, bore a $\frac{1}{4}$ "-diameter hole through the center of each drawer front.


3 With the drawer boxes inserted, place the applied fronts in their openings. Using each previously drilled $\frac{1}{4}$ "-diameter hole as a guide, bore a $\frac{1}{4}$ "-diameter hole through each drawer box front. A brad-point bit will minimize tear-out.

4 Remove the drawers, and install the pulls. Then drill and countersink the drawer box front for four $\#6 \times \frac{3}{4}$ " screws, where shown in **Figure 4**. Install the screws, and remove the pull.


5 Push each drawer completely into its opening against the



Saw the dados and grooves feeding with a miter gauge and using the rip fence as a stop.



Saw the rabbets with the stock standing on end. Use a raised featherboard to prevent tipping.



After repositioning the fence a hair closer to the blade, saw the bottom rabbets in the same fashion.



M For stability when routing the moldings, shape the edge of a wide piece of stock, and then rip it to final width. Keep a pushstick at hand for safe feeding.



N To clamp the moldings, use hot-melt glue to attach a stand-off strip to the thinnest section of the molding, and then span the molding with another strip used as a caul.

Tip Alert

When test-fitting drawers, apply one end of a strip of tape to the rear faces, with the opposite end extending from the cabinet front to serve as a temporary handle.


cabinet back, and cut two strips of wood a few inches long and equal in thickness to the inset. Then spot-glue these to the cabinet bottom behind each drawer to serve as stops. No need for clamping here; a rubbed joint is fine.

Add the moldings


- 1** Referring to the molding details in **Figure 1**, as well as the **Cut List**, cut the moldings (V, W) using your router table (**Photo M**).
- 2** Crosscut and miter each pair of bottom and top side moldings

Installing Double French Cleats


Step 1: After marking wall stud locations on the wall cleats, place them against the previously attached cabinet cleats.




Step 3: Remove the cleat/panel assembly, screw two wide boards to the opposite faces of the cleats (avoiding the wall stud locations), and then detach the panel.



Step 2: Screw a wide panel to the wall cleats to maintain their spacing.



Step 4: Place the cleat/board assembly against the wall, screw the cleats to the studs using 2½" screws, and then remove the boards. Hang the cabinet on the wall cleats.



Tip Alert

To cleanly release a hot-melt glue bond, pour a bit of denatured alcohol into the joint.

(V, W) to length, and glue them to the case sides. After the glue cures, fit the front sections and glue them in place, too (**Photo N**).

Finish up

1 Make the cleats (X) to the size in the **Cut List**, beveling one edge of each to 45°. Then rip away the knife edge, leaving a flat about 1/8" wide. Glue and screw two of the cleats through the back (E) and into the rear edges of their respective horizontal panels using 2 1/2" screws.

2 Sand the case, door, and drawer fronts through 220 grit, gently easing any sharp edges in the process.

3 Apply the finish of your choice. I wiped on one coat of General Finishes' Seal-A-Cell, followed up with two coats of the company's Arm-R-Seal topcoat.

4 Attach the ramps, installing all the screws this time.

5 Make the glass stop strips (Y, Z) to the sizes in the **Cut List**. Lay the door glass in its rabbets, and carefully tack the stop strips in place using 1/2" brads. Then hang the door, and drill for the pull.

6 Install the brass knobs and cupboard turn.

7 Hang the cabinet. Although using a single French cleat may do the job, I'm not taking any chances of it crashing to the floor filled with finely tuned hand planes, so I doubled up on the cleats. To ensure that each cabinet- and wall-cleat pair is carrying its fair share of the load, install the cleats as shown at left. ■

About Our Author/Builder/Designer

Geoffrey Noden has been working wood for over 30 years. The first American graduate of the John Makepeace School for Craftsmen in Wood in Dorset, England, Noden now builds custom furniture in Trenton, New Jersey. He is also the inventor of the Adjust-A-Bench and the Inlay Razor. For more info, visit adjustabench.com.

Hand Plane Cabinet

	Part	Thickness	Width	Length	Qty.	Mat'l
A	Sides	3/4"	12 7/8"	47"	2	OP
B*	Horizontal panels	3/4"	11 3/4"	25"	5	OP
C	Drawer divider	3/4"	4 1/2"	11 3/4"	1	OP
D*	Edging	3/4"	3 7/8"	25"	1	O
E	Back	1/2"	25"	47"	1	OP
F	Drawer guides	3/4"	3/4"	11 3/4"	2	O
G	Ramp panels	1/2"	9 1/2"	26"	2	OP
H	Ramp edging strips	1/4"	3/4"	26"	4	O
I	Ramp vertical divider strips	1/4"	3/8"	26"	4	O
J	Ramp rails	7/8"	1 3/8"	10"	2	O
K*	Face frame stiles	3/4"	2 3/8"	47"	2	O
L*	Face frame rails	3/4"	2"	21 1/4"	2	O
M*	Drawer box edging	3/4"	3/4"	26"	1	O
N	Door stiles	3/4"	2"	38 1/4"	2	O
O	Upper door rail	3/4"	2"	20 3/4"	1	O
P	Lower door rail	3/4"	2 1/2"	20 3/4"	1	O
Q	Door stop strip	1/4"	3/4"	24 1/2"	1	O
R	Drawer box sides	1/2"	4"	11 1/2"	4	P
S	Drawer box fronts and backs	1/2"	4"	9 3/4"	4	P
T	Drawer bottoms	1/2"	11"	9 3/4"	2	OP
U	Applied drawer fronts	1/2"	4"	10 1/4"	2	O
V*	Bottom molding	3/4"	3/4"	60"		O
W*	Top molding	1 1/4"	1 3/8"	60"		O
X	Cleats	5/8"	4"	25"	4	O
Y	Horizontal glass stop strips	1/4"	1/4"	17 3/4"	2	O
Z	Vertical glass stop strips	1/4"	1/4"	33 3/4"	2	O

* Indicates parts that are initially cut oversized. See instructions.

Materials: OP=Oak Plywood, O=Solid Oak, P=Pine

Convenience-PLUS BUYING GUIDE

<input type="checkbox"/> 1.	Whiteside 1807 Cove Router Bit 1/2"SH 3/4"R x 2"D x 7/8"CL	#811946	\$62.49
<input type="checkbox"/> 2.	Whiteside 1810 Cove Router Bit 1/2"SH 1"R x 2 1/2"D x 1"CL	#814814	\$96.99
Above items are available at Woodcraft stores, woodcraft.com or by calling (800) 225-1153. Prices subject to change without notice.			
<input type="checkbox"/> 3.	P-97 Antique Solid Brass Knob with 1 3/4" Long Brass Shank (2 needed)	#P-97-A	\$9.75
<input type="checkbox"/> 4.	H-97 Antique Cupboard Turn	#H-97-A	\$13.75
<input type="checkbox"/> 5.	HH-2 3 1/2" Antique Brass H Hinge (pair)	#HH-2-3.50-A	\$56.50
Above items are available at www.horton-brasses.com or by calling (800) 754-9127			



Learn 10 Tricks to Use Your
Combination Square
on our YouTube page at
youtube.com/lstarrett

Starrett®

121 Crescent Street • Athol, MA 01331
978-249-3551 • starrett.com

A Great Gift Idea!

Tough-Enough Bulldozer

Build an earth-moving playtime favorite.

By Tom Whalley and Marlen Kemmet



Overall Dimensions: 10 $\frac{3}{4}$ "w x 15"l x 8 $\frac{3}{8}$ "h

Whether pushing sand in the sandbox or blocks across the playroom floor, this mighty mover does it all. A lifting blade allows for easier maneuvering and the realistic treads lay down tracks just like the real ones. Expect to work with a lot of small parts. That means extra caution is in order. We'll walk you through the part making and assemblies one step at a time.

Note: For the tread, we went with $\frac{1}{2}$ "-wide tanned and oiled



*Latigo leather. It's supple and ideally suited for outdoor uses such as saddle parts. See the **Convenience-Plus Buying Guide.***

Ordering Other Tough-Enough Toys

To view and purchase the downloadable plans for the Tough-Enough Truck, Front-End Loader, and Road Grader, go to woodcraft.com.



Figure 1: Bulldozer Exploded View



Position the motor assembly over the frame and screw it in place. Use a block of wood to ensure the bottom edges are flush.

Start with the frame and motor

1 Laminate two pieces of $\frac{3}{4} \times 1\frac{3}{4} \times 12$ " maple together face-to-face to form a blank for the frame (A). Now, joint, rip, and crosscut the part to $1\frac{1}{2} \times 1\frac{3}{8} \times 10\frac{1}{2}$ ". (See **Figure 1** for reference.)

2 Cut the motor sides (B), hood (C), and grill (D) to the sizes in the **Cut List**. (We used a miter gauge, auxiliary fence, and stopblock, starting with extra long stock for safe cutting.)

3 To cut the grill grooves, install a flat-top blade and a zero-clearance insert (ZCI)

in your tablesaw, along with a miter gauge and auxiliary fence. Raise the blade $\frac{1}{8}$ " above the saw table. Lay out the groove locations (**Figure 2**), and cut the grooves.


4 Drill a pair of $\frac{7}{32}$ " holes in the grill for adding the headlights.

5 Using double-faced tape, adhere the motor sides (B) inside face to inside face, and drill the $\frac{7}{16}$ " and $\frac{3}{16}$ " holes where shown on **Figure 1**.

6 First dry-fit the motor assembly pieces (B, C, D), and then glue and clamp them together with the edges flush. Rout a $\frac{1}{4}$ " round-over

Figure 2: Parts View

For full-sized patterns, visit woodcraftmagazine.com.



along the top edges of the assembly (C, D). Bevel-rip the tapered bottom edge of the grill at 45° at the tablesaw.

Using the shank holes in the motor sides as guides, drill $\frac{7}{64}$ " pilot holes into the sides of the frame. Screw the motor to the frame (**Photo A**).

7 Cut the platform (E) to size. Drill the 12 mounting holes where shown on **Figure 2**. Cut the centered groove and rabbets at the tablesaw where shown, using a dado set, ZCI, and pushblock. Screw the platform to the top of the frame, flushing the back edges.

Add the cab and fuel tank

1 To form the cab sides (F), mill a piece of maple to $\frac{1}{2} \times 3\frac{5}{8} \times 8$ ". To form the cab (window) dividers and cab corners (G), cut a $\frac{1}{4} \times \frac{1}{4} \times 24$ "-long piece of walnut stock. To cut the cab front and back (H), mill a piece of maple stock to $\frac{1}{2} \times 3 \times 8$ ".

2 Referencing **Figure 3**, cut a $\frac{1}{4}$ " groove, $\frac{1}{4}$ " deep, on one face of the blank for the cab sides (F). Cut the $\frac{1}{4}$ " rabbets, $\frac{1}{4}$ " deep on the cab front and back (H) where shown.

3 Crosscut an 8"-long piece from the dividers and corner blank for parts (G) and glue it in the groove


in the cab sides (F) blank.

Crosscut two cab sides (F/G) to length from the blank. Cut the




Glue and clamp the cab corners into the rabbets, holding them snugly in place with spring clamps.

Figure 3: Cab Exploded View



remaining walnut stock for the cab corners (G) to 3½". Crosscut the cab front and back blank for (H) to 3½". Now, glue and clamp the assembly together (F, G, H) in the configuration shown in **Figure 3** and **Photo B**. Make sure that the groove is 1½" from the assembly's back side.



Fit the fuel tank assembly onto the platform and flush at the rear end. Screw it in place.

4 From ¼"-thick walnut, cut the cab top and bottom (I) to size. Glue these pieces to the cab assembly. Rout ¼" round-overs on the cab where shown. Note where the rear cab corners (G) are not rounded over to accommodate the fuel assembly. Cut the cab roof (J) to size, and rout ⅛" round-overs along all edges.

5 Cut the fuel tank sides (K) and back (L) to size, cutting the length of L to the same width as the assembled cab. (I laminated ¾"-thick stock for the back tank.) Glue-join the parts and let them setup. Then, bevel-cut the top

back edge of the assembled tank at the tablesaw using a pushblock. Drill a ⅞" hole in the back (L) for adding the fuel cap later. At the router table, rout ⅛" round-overs, where shown on **Figure 1**. Edges that touch the cab assembly or platform do not get round-overs. Screw the fuel tank assembly to the platform (**Photo C**).

6 Finish-sand and apply finish to the frame assembly (A-E, K, L). (We sprayed on Watco Lacquer, Satin.)

7 Center, glue, and clamp the roof (J) to the cab assembly (F-I). Finish-sand the assembly. Screw the cab assembly (F-J) to the platform (E). Sand a ⅛" round-over on the back two corners of the platform to match the fuel tank assembly. Note that the fuel tank fits flush with the end of the platform. Apply finish.

Build the blade lift assembly

1 Cut the two blade lift arms (M) to the shape shown in **Figure 2**. Mark the three hole centerpoints on each and drill the holes.

2 Cut the handle (N) and pivot pin (O) to length from dowel stock noted in the **Cut List**. Drill a ⅛" pilot hole centered in each end of each dowel. (We used a center finder.) Glue and screw the handle and pivot pin to one of the lift arms (M). Apply a finish.

3 Cut the two front spacers (P) from ¾" walnut dowel stock. Drill a ⅞" hole centered through each. Cut the lift pin (Q) to size from ⅜" dowel stock. Apply finish to the remaining parts (M, P, Q).

4 Slide the lift pin (Q) through the blade lift arms (M). Fit the front spacers (P) onto the ends of the lift pin.

5 Fit a ⅜" nylon washer onto the pivot pin (O). Position the

Tip Alert

After assembling the cab, we taped a sheet of 120-grit sandpaper to a flat surface and rubbed the top and bottom of the assembly on it to even the edges and remove glue squeeze-out.




Figure 5A: Track Shoe Blank Cutting Sequence




Figure 5B: Adding the Tread Leather





Figure 5C: Completing the Tracks

Construct the tracks

- 1** From $\frac{1}{2}$ " walnut stock, cut the track shoe blank (Y) to 3" wide by 22" long.
- 2** To cut evenly spaced kerfs, make an auxiliary miter-gauge fence with a protruding $\frac{1}{8} \times \frac{1}{8}$ " finger $\frac{3}{4}$ " from the blade. (We used the flat-top blade.) Use scrap stock to verify that the kerfs are cut exactly $\frac{3}{4}$ " apart. Cut extra scrap to verify the test cuts in **Step 3**. Now, cut $\frac{1}{8}$ " kerfs, $\frac{3}{8}$ " deep and $\frac{3}{4}$ " apart, along the entire length of the blank. See **Figure 5A**.
- 3** Lower the blade for a $\frac{1}{16}$ "-deep cut. Next, slide the auxiliary fence over so that the $\frac{1}{16}$ " kerfs to be cut for receiving the cleats (Z) will be accurately centered between two $\frac{3}{8}$ " deep kerfs. Now, using the test pieces made in **Step 2**, cut $\frac{1}{8}$ " kerfs, $\frac{1}{16}$ " deep. Once verified, cut the kerfs in the track shoe blank, as shown in **Photo E**.
- 4** Cut enough $\frac{1}{8} \times \frac{1}{8}$ " walnut for the 24 cleats (Z). Now, at the bandsaw, crosscut the cleats to 3", and glue them into the $\frac{1}{16}$ "-deep kerfs. Remove any glue squeeze-out.
- 5** Bandsaw two equally wide strips from the 3"-wide blank, using a fence to ensure accuracy.
- 6** Bandsaw each strip to $1\frac{1}{4}$ " wide, trimming the edges opposite the bandsawn edges from **Step 5**. Sand the edges of both strips smooth to remove the saw marks.
- 7** Cut a $\frac{9}{16}$ " groove, $\frac{5}{32}$ " deep, down the center of each $1\frac{1}{4}$ "-wide strip.
- 8** Drill two rows of $\frac{3}{64}$ " holes through the center of each cleat (Z) $\frac{15}{32}$ " from the edge of the tread blank. Bandsaw two track shoes from the end of each strip.
- 9** Cut the support jig base to the size shown on **Figure 5B**. Cut a $\frac{1}{4}$ " groove, $\frac{1}{8}$ " deep, down the center of the support. Cut




E At your tablesaw, use an auxiliary miter-gauge fence and protruding $\frac{1}{8} \times \frac{1}{16}$ " finger to cut evenly spaced kerfs for the cleats (Z).



F Drive brads through the $\frac{3}{64}$ " holes and alongside the support strip.



G Bend the brads over to secure the treads to the leather strip.



H Use a pushblock and sideblock to support the long track shoe strip when cutting.

a $\frac{1}{4} \times \frac{1}{4}$ " rib to fit into the groove. Glue the rib in place.

10 Using a sharp utility knife, crosscut two pieces of $\frac{1}{2}$ "-wide leather to 24" long for the tread leather (AA).

11 Center the trimmed track shoe blank (Y) onto the leather strip (AA). Using $\frac{3}{4}$ " brads, drive a brad through each hole to securely nail the track to the leather strip (**Photo F**).

12 Flip the track assembly over and bend the brads toward the center of the track (**Photo G**). Lightly pound the bent ends flat into the leather.

13 Set the saw blade height to cut along the bottom edge of the leather, but not into the leather, to create the track shoes (**Photo H**).


14 Bandsaw the final four track shoes from the piece cut in **Step 8**.



I Notch the ends of the leather strip to mate together.

15 Using a sharp utility or razor knife, split then notch the mating ends on the leather strip nailed to the walnut tracks, as shown in **Figure 5C** and **Photo I**. Note that the notches are mirror images of each other.

16 Using Tanner's Bond Craftsmen Contact Cement, adhere




J Using spacers and edge guides, brad the final two tracks to the leather strip.

the two mating ends of the leather together using small clamps. Allow the glue to get tacky.

17 Using $\frac{1}{8}$ "-thick spacers for even tread placement, brad the two remaining track shoes over the notched leather ends (**Photo J**). Clinch the ends as before.

Figure 6: Blade Assembly




Blade lift arm

- 1** Cut the pusher main frames (BB) to shape (**Figure 2**). Mark the $\frac{7}{16}$ "-wide slot locations, drill holes at each slot end, and cut out the waste at a scrollsaw. Now, drill a $\frac{7}{16}$ " axle peg hole and the $\frac{3}{16}$ " shank holes in each. Rout a $\frac{1}{8}$ " round-over on all but the front edges of BB.
- 2** From $\frac{3}{4}$ " maple dowel, crosscut the rear spacers (CC) to $\frac{1}{4}$ " thick, and drill a $\frac{3}{8}$ " hole centered in each (**Figure 1**).
- 3** Cut the blade-mounting bracket (DD) to size. Rout an $\frac{1}{8}$ " round-over on the top and bottom inside edges. Clamp that part between the main frames (BB), centered top to bottom with the front edges flush. Use the shank holes in each BB to drill mating pilot holes in each end of DD. Part AD will be added later.
- 4** Finish-sand (BB) and (DD). Apply finish to all but the front surfaces of (BB) and (DD) where the blade will attach later.

Create the blade

- 1** Cut the blade bottom blank (EE) and blade blank (FF) to the sizes noted in the **Cut List** and shown in **Figure 6**, bevel-ripping one edge of EE where shown. Glue the two pieces together.
- 2** Bevel-cut the ends of the blade assembly (EE, FF) at 15°. Cut the side plate blanks (GG) to size (**Figure 2**). Glue one to each end



With the tread tightened against the wheels, screw the front axle assembly to the frame bottom.

of the blade assembly. Sand the side plates flush with the front and back of the blade. Finish-sand the blade assembly.

Final assembly

- 1** Position the bulldozer upside down on a soft cloth on your workbench to prevent scratching the cab top. Screw the rear axle (S) to the frame bottom $\frac{1}{4}$ " from the back end.
- 2** Position, but don't screw, the track roller assembly (T, W, X) and front axle assembly (R, U, V) on the frame. Place the two track assemblies over the front axle and track roller assemblies. Slide a $\frac{3}{8}$ " nylon washer onto each end of the lift pin (Q). Now, add the pusher main frame pieces (minus the blade mounting bracket [DD]) to the rear axle as shown in **Figure 1**, gluing the axle pegs into the rear axle (S). I applied glue into the holes in the



Spring clamps work well to clamp the blade to the blade mounting bracket.



rear axles (S) with a Q-tip, making sure the wheel assemblies turned freely.


3 Snug the track assemblies to the front axle assembly (R, U, V) with a small clamp. Then using the slots in the front axle assembly as guides, drill a pair of $\frac{7}{64}$ " pilot holes into the bottom of the frame, positioning the bit in the middle of each slot. Drive the two front screws as shown (**Photo K**).

Center the track roller assembly between the front and rear axle assemblies and screw it in place.

4 Screw the blade mounting bracket (DD) between the pusher main frames (BB).

5 With the blade lift assembly vertical, center and glue the blade assembly to the front of the main pusher frame (**Photo L**).

6 Mask off the front end of the bulldozer and apply finish to the blade. Let it dry and turn the toy over to the up-and-coming builder in the family. ■



About Our Designer/Builder
Urbandale, Iowa, resident Tom Whalley has been a

woodworker for over 40 years and is the current president of the Des Moines Woodworker's Association. His award-winning designs have been featured in several national woodworking publications. Creating unique "one-of-a-kind" projects is Tom's focus.

Bulldozer Cut List

	Part	Thickness	Width	Length	Qty.	Mat'l
A*	Frame	1½"	1⅜"	10⅜"	1	M
B	Motor sides	½"	3⅜"	4⅞"	2	M
C	Hood	½"	2½"	4⅞"	1	W
D	Grill	⅜"	3⅞"	2½"	1	M
E	Platform	¾"	5"	5⅝"	1	M
F*	Cab sides	½"	3⅝"	3½"	2	M
G*	Cab dividers/corners	¼"	¼"	3½"	6	W
H	Cab front and back	½"	3"	3½"	2	M
I	Cab top/bottom	¼"	3½"	4⅞"	2	W
J	Cab roof	½"	3⅞"	4⅝"	1	W
K	Side fuel tanks	¾"	1¾"	3¼"	2	M
L	Back fuel tank	1½"	1¾"	3½"	1	M
M	Blade lift arms	½"	1"	7"	2	W
N	Handle		1" dowel	2⅝"	1	W
O	Pivot pin		⅜" dowel	2⅝"	1	M
P	Front spacers		¾" dowel	1½"	2	W
Q	Lift pin		⅜" dowel	7¾"	1	W
R	Front axle	¾"	1½"	4"	1	M
S	Rear axle	¾"	¾"	4"	1	M
T	Track roller axle	¾"	1½"	3½"	1	M
U*	Wheel outer	¼"	2⅞" dia.		8	M
V*	Wheel inner	⅞"	2⅞" dia.		4	M
W	Center frames	½"	1⅞"	3⅜"	2	M
X	Track rollers	½"	1" dowel		10	M
Y*	Track shoe blank	½"	3"	22"	1	W
Z	Cleat blanks	⅛"	⅛"	80"	1	W
AA	Tread leather	⅜"	½"	24"	2	L
BB	Pusher main frames	½"	2"	12⅞"	2	M
CC	Rear spacers		¾" dowel	¼"	2	M
DD	Blade mounting bracket	½"	1⅝"	6¾"	1	M
EE	Blade bottom blank	¾"	1"	10¾"	1	W
FF	Blade blank	½"	3"	10¾"	1	M
GG*	Side plate blank	¼"	2⅞"	3¾"	1	M

* Indicates parts initially cut oversized. See instructions.

Materials: M=Maple, W=Walnut, L=Leather

Hardware/Supplies: (10) ¼" nylon washers; (10) ⅜" nylon washers; (20) #8 × 1¼" flathead screws; (6) #8 × 1½" roundhead screws; (96) ¾" brads; ⅜" maple dowel stock; ¼" maple dowel stock; ¾" walnut dowel stock; 1" maple dowel stock; 1" walnut dowel stock; 2⅜" holesaw; 2⅞" holesaw; ⅞" - 6" medium holesaw mandrel.

Convenience-PLUS BUYING GUIDE

<input type="checkbox"/> 1.	Freud LM72M010 10" Flat Top Saw Blade	#127238	\$54.97
<input type="checkbox"/> 2.	Watco Lacquer, Satin, Spray, 11.25 oz. aerosol can	#146950	\$9.99
<input type="checkbox"/> 3.	Groz Steel Center Finder	#143559	\$34.99
Above items are available at Woodcraft stores, woodcraft.com , or by calling (800) 225-1153. Prices subject to change without notice.			
<input type="checkbox"/> 4.	Axle Pegs, 2⅞" L, 1½" Tenon, Bag of 12	#AP3500	\$3.00
<input type="checkbox"/> 5.	Axle Pegs - 1½" L, 1⅝" Tenon, ⅜" head, 20/Pkg	#AP1003	\$1.50
Available at Woodworks Ltd., craftparts.com , or by calling (817) 581-5229. Prices subject to change without notice.			
<input type="checkbox"/> 6.	Latigo Cowhide Leather Strap ½" (1.3cm) × 72"	4752-00	\$17.99
<input type="checkbox"/> 7.	Tanners Bond Craftsman Contact Cement	2525-01	\$15.99
Available at Tandy Leather, tandy Leatherfactory.com , or by calling (877) 532-8437. Prices subject to change without notice.			

Holiday Carousel

Add a warm glow to the season with this intriguing heat-actuated decoration.

Designed and built by Tom Whalley
Written by Marlen Kemmet



Overall Dimensions: 8½"w × 8½"l × 11¼"h

The Christmas pyramid (or holiday carousel), a decoration that originated in the Erzgebirge (Ore Mountains) of Germany, has now taken root in this country, serving as an eye-catching centerpiece. It typically depicts either a Christian or secular motif such as a Nativity or charming winter scene (like the one shown here). While many buy such a table whirligig online, we developed a totally unique

design for you to build, and we include patterns and processes to help shape the parts safely and accurately. Once assembled and pressed into service, you'll find onlookers enjoying how the heat from the candles propels the fan, which, in turn, rotates the evergreen tree and snowmen.

Start with the base

1 Lay out and cut the octagonal walnut base (A) to shape on the

bandsaw, referring to **Figures 1 and 2**. On the top center of the base, use a Forstner bit to drill a ⅝" hole, ⅓" deep for the pyramid disk glass bearing. Then, drill a ⅛" guide hole through the center of that. On the bottom, drill the 1⅝" hole ⅓" deep. **2** Rout a ¼" round-over along all top edges of the base. Sand smooth. Glue the pyramid disk glass bearing into the hole in the bottom of the base.



A Adhere the full-sized pattern to the maple lamination, and bandsaw the two curved supports from it.



B Locate a combination square on the piece of 2x4 where shown, and mark the top cutline on a clamped curved support.

Add the curved support pieces

1 Laminate two pieces of $\frac{3}{4}$ "-thick maple together face-to-face to create a blank $2\frac{1}{4}$ " wide by $8\frac{1}{2}$ " long for the curved supports (B). (See **Figure 2**.) adhere the full-sized pattern to the blank. Now, bandsaw outside the cutline (**Photo A**), and then drum- and disc-sand to the line.

2 Clamp a curved support (B) to a piece of 2x4. Mark a line $2\frac{3}{8}$ "

Figure 1: Carousel Exploded View





Figure 2: Parts View and Patterns



from the end of the 2×4. Place a square on the 2×4, where shown (**Photo B**), and mark the cutline at the support's top end. Repeat for the other support. Bandsaw the top ends where marked.

3 To make the notching guide, cut a piece of 2×4 to 2³/₈" wide by 10" long. Trace the inside edge of a curved support (B) on the



Using a curved block at the tablesaw, cut the centered 1/4"-wide notch in the top end of each support in two passes.

guide's face, starting at one end. Now, bandsaw the 2×4's curve to shape. Add a pair of cleats to the guide to hold the curved support in place when notching. Next, position a curved support on the guide, adjust the fence as needed, and cut a centered 1/4" notch, 1/8" deep, in the top end. Repeat for the second curved support, as shown in **Photo C**.

4 Referring to the dimensions in **Figure 2**, lay out the tapers on both curved supports (B), using the edge of one support as a straightedge for the other. Then scrollsaw and sand the supports to shape.

5 Center, glue, and clamp the curved supports (B) to the long-grain edges of the base. Dry-fit the two curved supports together, and align them at the top. Dab glue onto the notched ends, and secure them together with painter's tape.

Create the platform and tree

1 Lay out the round platform (C). Drill a centered 3/64" hole in the part. Bandsaw, and sand the platform to shape.

2 Resaw enough walnut (**Photo D**) to create three pieces of 1/16"-thick stock to form two three-ply laminations that measure 4¹/₈" by 5⁷/₈" for each tree half (D). (We worked from a longer board and then cut the two sets of plies to size. We also resawed the plies a little thicker and sanded them down to the needed thickness. You can also use layers of store-bought veneer for this.)

3 Sand the ply surfaces smooth. For each tree lamination blank, glue up three plies face-to-face for a finished thickness of 3/16", alternating the grain of the center ply at 90° to the outside plies (**Photo E**). For perfectly



D Using a simple bull-nose guide, resaw thin walnut plies at the bandsaw to make the tree blanks.



E Laminate three plies of $\frac{1}{16}$ " resawn walnut for each tree blank, alternating the grain.

flat panels, we clamped the blanks between two pieces of $\frac{3}{4}$ " MDF and waxed paper. (This shop-made plywood offers added strength and resistance to breakage when scrollsawing the branches.)

4 Adhere a full-sized pattern to each tree lamination. Using a #7 skip-reverse-tooth blade, scrollsaw the two tree profiles to shape (**Photo F**), cutting a notch in the top of one and a mating notch in the bottom of the other (see **Figure 1**). Fit the two pieces together so the top and bottom edges are flush. Now, glue them together, wiping off any excess. Sand the top and bottom edges flush.

5 Carefully indent a center point, and drill a $\frac{5}{64}$ " hole, $\frac{1}{4}$ " deep, in the center in the bottom of the tree, and a $\frac{3}{32}$ " hole, $\frac{1}{4}$ " deep, in the tree top (**Figure 1**). Apply a clear finish to all but the bottom of the assembled tree.

Now for the snowmen

1 Cut the snowmen blank bottoms (E) and tops (F) to size; cut an extra $\frac{3}{4}$ " square blank for the hub top (N) to use later. For the hats (G) cut two pieces of $\frac{3}{4}$ " walnut to 6" long. At a belt sander or belt strip sander, sand a hat to shape, rotating the dowel's end on the edge of the belt. Similarly, sand the dowel's other end. Sand a facet or two for a crumpled

look. Repeat on a second dowel. Crosscut the four hats to length from the dowel stock, sawing $\frac{1}{8}$ " beyond the sanded cylinders to create the brim.

2 Drill a $\frac{1}{4}$ " hole through the center of each snowman blank (E, F). Drill a $\frac{3}{8}$ "-deep hole in one end of the hub top blank for part (N).

3 Dry-fit a blank on the end of a $\frac{1}{4}$ " dowel, 8" long. (Use the dowel as a handle for safe sanding.) Now, sand facets on the edges of the blank (**Photo G**). Repeat for all of the snowmen top and bottom blanks (E, F), as well as the hub top (N).

4 Mark the hole locations for the eyes, nose, and smile. At the drill press, drill $\frac{5}{64}$ " holes,




F Scrollsaw the two tree halves to shape, cutting on the pattern's cutlines.



G Clamp a belt sander to the workbench, and facet the blanks all around to create a rustic chip-carved look.

Figure 3: Carousel Cross Section



$\frac{1}{8}$ " deep, in the snowman head pieces (F) while holding the parts on the dowel. Color the ends of two round toothpicks orange, and cut them to $\frac{1}{4}$ " long for the nose. Color the eyes and nose black (**Figure 1**). Glue in the toothpick eyes and smile pieces, allowing the toothpicks to be exposed about $\frac{1}{16}$ ". Cut them off. Insert the carrot nose.

5 Cut four snowman center pins (H) to size. Glue and dowel the bottom and top (E, F) snowman pieces together.

Add the hats (G). Apply a clear finish to each of the snowmen.

6 Insert a $\frac{3}{4}$ " brad through the hole in the platform (C) so the end extends about $\frac{1}{4}$ " below the platform (**Figure 3**). Glue the tree onto the head of the protruding brad so the tree is centered on the platform. Uniformly position and glue the four snowmen onto the platform.

Add the arch top and hub

1 Cut the arch top (I) to size to fit between the notches in the curved supports (B). Drill a $\frac{1}{8}$ " hole centered through the length of the piece.

2 Position the platform assembly onto the base assembly. Position the arch top (I) between the supports (B) and glue it in place (**Figure 1**). There should be a $\frac{1}{8}$ " gap between the bottom of the arch top (I) and the top of the tree.

3 Cut a piece of $\frac{1}{2}$ " stock to $1\frac{1}{4}$ " square, and adhere the full-sized hub (J) pattern in **Figure 2** to one face. Bandsaw and sand the hub to shape, holding the part with a small handscrew for safety. Then, as shown in **Photo H**, drill eight $\frac{1}{4}$ " holes, $\frac{1}{4}$ " deep, centered on each edge. These will house the fin pins (L). Now,

drill a centered $\frac{1}{4}$ " hole through its face. Sand and finish the hub.

4 Cut eight pieces of $\frac{1}{16}$ " plywood to $1\frac{1}{2} \times 3\frac{3}{4}$ " and stack them together using double-faced tape. Apply the full-sized pattern in **Figure 2** for the fan fins (K) to the top piece and then stack-cut the pieces at the scrollsaw. Sand the edges smooth, and separate the fins.

5 To create the eight dowel fin pins (L), start with a few lengths of $\frac{1}{4}$ " dowel stock. Test-fit the dowel stock in a hole in the hub and sand to fit. Bandsaw a $\frac{5}{8}$ "-deep kerf in the ends of the dowel to match the thickness of the fan fins (**Photo I**). Sand a slight round-over on the kerfed dowel ends, and crosscut the fin pins to 1" long.

6 Center and glue the fan fins (K) to the pins. Then, using a toothpick to work the glue in the holes, glue the fan/fin assemblies (K/L) to the hub (J), angling them at 30° from horizontal (**Photo J**).


7 Crosscut the hub pivot stem (M) from $\frac{1}{4}$ " dowel stock. Drill a centered $\frac{3}{32}$ " hole, $\frac{1}{2}$ " deep, into the stem's bottom end (**Figure 1**). (We marked a centered hole with a nail to prevent the bit from skittering off course and used a hand screw clamp to hold the workpiece perfectly vertical when drilling.) Using CA, glue the pivot stem into the hub (J) so the top end of the dowel extends $\frac{1}{4}$ " above the top surface of the hub.

8 Retrieve the faceted hub top (N) made earlier, and glue it on to the top end of the hub pivot stem (M). As a fire safety precaution, do not apply finish to the fan assembly.

9 Sand the head of a 6d (2") finish nail to the same diameter as the shaft without shortening the nail. Glue the nail into the hole in the hub pivot stem (M) using CA.



Use this simple jig setup at your drill press to clamp the hub firmly in place. Then drill consistent centered holes on each edge.



Use a block to press the dowel firmly against the spacer when advancing its end into the blade to create a centered kerf.



Employ this simple setup that includes a 30° angle guide to keep the fin angles consistent during the glue-up.

Make the feet and complete the assembly

1 Cut a piece of $\frac{3}{4}$ " walnut to $1\frac{1}{2}$ " wide by $5\frac{1}{4}$ " long for the feet blank (**Figure 2**). Mark the centerpoints, and drill a pair of $\frac{1}{2}$ " holes through the blank. Mark the centerpoints, and drill four $\frac{5}{8}$ " holes, $\frac{5}{16}$ " deep, for housing the candle cups later. Bandsaw four feet from the blank. (They'll end up just under $\frac{3}{4}$ " wide.) Sand them smooth.

2 Glue and clamp each foot (O) to the base assembly. Apply finish to the assembly, masking off the top surface of the glass bearing. Slide a candle cup through a dish, and epoxy it to a foot. Repeat for each foot.

3 Position the platform assembly on the base. Slide the 6d nail of the fan assembly through the hole in the arch top (I) and into the hole in the tree top. Maintain the $\frac{1}{32}$ " gap noted in **Figure 3**. Adjust the nail slightly in the pivot stem (M) if needed. Insert the candles. ■

Safety Alert

Do not leave burning candles unattended! This carousel is not a toy and is for indoor use only.

Candle Carousel Cut List

	Part	Thickness	Width	Length	Qty.	Mat'l
A	Base	$\frac{3}{4}$ "	$4\frac{3}{4}$ "	$4\frac{3}{4}$ "	1	W
B*	Curved supports blank	$1\frac{1}{2}$ "	$2\frac{1}{4}$ "	$8\frac{1}{2}$ "	2	M
C	Platform	$\frac{1}{4}$ "	4" dia.		1	BBP
D	Tree blanks	$\frac{1}{16}$ "	$4\frac{1}{8}$ "	$5\frac{7}{8}$ "	6	W
E	Snowman bottom blanks	$1\frac{1}{8}$ "	$1\frac{1}{8}$ "	$1\frac{1}{8}$ "	4	M
F	Snowman top blanks	$\frac{3}{4}$ "	$\frac{3}{4}$ "	$\frac{3}{4}$ "	4	M
G*	Hats		$\frac{3}{4}$ " dowel	$\frac{1}{2}$ "	4	W
H	Snowman center pins		$\frac{1}{4}$ " dowel	$1\frac{7}{8}$ "	4	M
I	Arch top	$\frac{1}{4}$ "	$\frac{1}{4}$ "	1"	1	M
J	Hub	$\frac{1}{2}$ "	$1\frac{1}{4}$ "	$1\frac{1}{4}$ "	1	M
K*	Fan fins	$\frac{1}{16}$ "	$1\frac{3}{8}$ "	$3\frac{1}{2}$ "	8	BBP
L*	Fin pins		$\frac{1}{4}$ " dowel	1"	8	M
M	Hub pivot stem		$\frac{1}{4}$ " dowel	$2\frac{3}{8}$ "	1	M
N	Hub top	$\frac{3}{4}$ "	$\frac{3}{4}$ "	$\frac{3}{4}$ "	1	M
O**	Feet blank	$\frac{3}{4}$ "	$1\frac{1}{2}$ "	$5\frac{1}{4}$ "	1	W

* Indicates parts initially cut oversized. See instructions.

** Note that four feet are cut from the foot blank. See **Figure 2**.

Materials: M=Maple, W=Walnut, BBP=Baltic Birch Plywood

Hardware/Supplies: (1) 6d (2") finish nail; (1) $\frac{3}{4}$ " brad; epoxy; CA glue; $\frac{1}{4}$ " maple dowel; $\frac{3}{4}$ " walnut dowel; round wooden toothpicks.

Convenience-PLUS BUYING GUIDE

<input type="checkbox"/> 1.	Birch Plywood $\frac{1}{16}$ " x 6" x 12"	#50W18	\$9.49
Above item available at Woodcraft stores, woodcraft.com or by calling (800) 225-1153. Prices subject to change without notice.			
<input type="checkbox"/> 2.	Pyramid Disk Glass Bearing	RPCUPDISK1X12	\$10.48
<input type="checkbox"/> 3.	Brass Drip Cup 14mm; (4) needed	RPBRUPX14	\$5.96
<input type="checkbox"/> 4.	Brass Drip Catcher 38mm; (4) needed	RPBRDRIP38X16	\$7.96
<input type="checkbox"/> 5.	German Pyramid Candles Medium White 14mm; (50/box)	CDD050X500XW	\$15.98
Available at ChristKindl-Markt, christkindl-markt.com or by calling (717) 889-2018. Prices subject to change without notice			

Handy Magazine
2013 Innovation Award
Honorable Mention

**Winner of 2013
AWFS Visionary
Award**

Change the way you build!

Water free formula!

- Clamp, sand and finish in minutes
- No activator required
- Minimizes clamping time
- Developed for joinery



Available in 3-Handling times & 1 fl. oz.; 4 fl. oz.; 16 fl. oz.

Nexabond™
INSTANT WOOD
ADHESIVE **2500**

422 Wards Corner Rd, Suite B
Loveland, OH 45140 • (513) 453-0100
nexabond.com • sales@nexabond.com

Learning by Doing

Connecticut Valley School of Woodworking

Bob Van Dyke – Director

*Featuring hands-on
classes for all skill
levels taught
by nationally
known craftsmen
including*




table by guest instructor Steve Latta

Phil Lowe
Will Neptune
Steve Latta
Peter Galbert
and more!

249 Spencer St., Manchester, CT 06040

860.647.0303

www.schoolofwoodworking.com

WOODCRAFT®

**QUALITY WOODWORKING TOOLS •
SUPPLIES • ADVICE®**

NEW Kojent Pen Kits

Wow, elegant, and impressive are just a few words that describe the Kojent Pen Kits. These well balanced, two-piece pen kits provide a variety of pen style and plating options. The simplistic but elegant kit design features high quality platings, ink refills, and double twist mechanisms. You are sure to find several kits you want to turn into pens for your family and friends – and yourself.

- 159743 Fountain Pen Cobalt Gold & Chrome
- 159744 Fountain Pen Cobalt Gold & Gunmetal (A)
- 159745 Rollerball Chrome & Gunmetal
- 159746 Rollerball Cobalt Gold & Chrome
- 159747 Rollerball Cobalt Gold & Gunmetal
- 159748 Rollerball Gunmetal & Cobalt Gold (B)
- 159749 Ballpoint Cobalt Gold & Chrome (C)
- 159750 Ballpoint Chrome & Gunmetal (D)
- 159751 Ballpoint Cobalt Gold & Gunmetal
- 159752 Ballpoint Gunmetal & Cobalt Gold

Pen Blanks sold separately.



Elegant
Features



High Quality
Plating



To Find Your Local Woodcraft Store Or For A Free Catalog, Visit woodcraft.com Or Call 1-800-225-1153.
For Information On Woodcraft Retail Franchise Opportunities, Visit woodcraftfranchise.com

15WD01H

Thomas Flinn & Co.

Saw & Hand Tool Manufacturer
Sheffield, England



The perfect way to cut logs the traditional way.

The Lynx saw range –
Available at Woodcraft

www.flinn-garlick-saws.co.uk
orderonline@flinn-garlick-saws.co.uk
Tel: +44 114 2725387

SABURRTOOTH® SUPERIOR POWER CARVING TOOLS

- RAPID STOCK REMOVAL • LONGER-LASTING
- NON-LOADING • SMOOTH-OPERATION
- EASIER TO CONTROL • MORE AGGRESSIVE
- VERSATILE

Available at participating
Woodcraft locations



Visit our distributors page at:
WWW.SABURRTOOTH.COM


Select your Elite bench with **free storage cabinet!**



ELITE 2500
\$2,215
Length 99"



ELITE 2500 Workbench + free Cabinet SM08.
Worth \$ 535. Weight 371 lbs.



WOODCRAFT®

For a free catalog or
to find your local
Woodcraft Store,
visitwoodcraft.com or
call 800-225-1153.

Rock solid and packed with features

- Designed and built by Swedish craftsmen
- European beech top and trestle
- Top 3 1/4" thickness with 4 1/4" skirt
- Massive 29" full width vises
- Double row of 1" round steel bench dogs



ELITE 2000 Workbench
+ free Cabinet SM08.
Worth \$ 535

ELITE 2000
\$2,060
Length 76"



ELITE 1500 Workbench
+ free Cabinet SM07. Worth \$ 427

ELITE 1500
\$2,000
Length 59"



sjobergs.se

Available in November and December whilst stocks last.



Wood River®



Introducing The WoodRiver® HD Shelf System

The WoodRiver® HD Shelf System is a truly unique shelving option that is made from steel tubing and powder coated to give a long lasting finish. The shelves are movable in 6" increments along the 44"-long, 1 $\frac{5}{8}$ "-diameter uprights and can be stacked to provide a full wall of shelves. Additional shelves (158998) can be purchased to offer even more storage space for your garage, shop, utility room, and storage building.

- Heavy-Duty Construction With Three Movable Shelves
- 12" Shelf Brackets Are 12" Long, 1 $\frac{1}{8}$ " Square, Slightly Angled And Can Conveniently Rotate 90° Inward Or Outward For Easy Storage When Needed
- System Holds Up To 1,200 Lbs. When Securely Installed Or Up To 400 Lbs. Per Shelf
- Includes Two Uprights, Three Shelves With Hardware, Plastic Wall-Mount Spacers
- Recommended Distance 4' - 6' Between Uprights
- Wall-Mount Hardware Not Included

158999 3-Shelf System (A)

158998 Additional Shelf Bracket Set



WOODCRAFT® HELPING YOU MAKE WOOD WORK®

15WD01P3

For A Free Catalog Or To Find Your Local Woodcraft Store, Visit woodcraft.com Or Call 800-225-1153.
For Information On Woodcraft Retail Franchise Opportunities, visit woodcraftfranchise.com



Specialty Chisels

15 sharp problem-solvers for all sorts of tricky cuts

By Joe Hurst-Wajszczuk

Many of us remember the set of basic bevel-edged chisels that started our pursuit of fine woodworking. Likewise, we may recall encountering the first chores that required the touch of a different kind of chisel.


But selecting these newcomer specialists for our chisel arsenals can be tricky. Although a chisel is fundamentally a simple tool, over the years it has morphed into myriad configurations to suit specific tasks. The choices can be overwhelming, and selecting the wrong ones can be expensive.

Here, I've turned the focus on function. Seeing what each tool is used for can help you appreciate certain attributes and shine a light on the ones that you need to make quicker, cleaner cuts on your projects.

Toolbox/Jobsite Companions

A sharp chisel is essential for a variety of chores, such as mortising hinges, adjusting trim, and cleaning up cuts. In addition, "jobber" chisels help ensure that your good set stays safe at your bench.

Short butt chisels are easy to control and stash in a pocket or pouch. If you prefer a longer blade, FastCap's folding handle shields the edge from receiving (and causing) damage, but is sturdy enough to withstand metal hammer blows. For quicker mortises, a corner chisel registers against the lip of routed mortises and finishes the corner with a tap.



WoodRiver Butt Chisel Set
152169, \$59.50

WoodRiver
Corner Chisel
#143717, \$19.99

FastCap PC-1 1-Inch Pocket Chisel,
\$22.99, Amazon.com

Medium-Duty Mortisers

Mortising chisels were designed to handle the abuse of being malleted into the wood and then levered to remove waste. Modern machinery has eliminated the need to own a full set, but having a few can help you tackle chores that would blow out your bench chisels or require a pricey jig.

Sash chisels rank as middle-weights in the mortising chisel arena, but these former window-makers are nicely suited for most furniture-scale joinery. With thick blades (typically ground with 30° bevels) and unbreakable handles, sash chisels can easily handle shallow mortises with just a mallet. For deep mortises, this is the chisel you'd reach for



Henry Taylor Swan-Neck Chisel, 1/4"
58S07.01, \$33.50, leevalley.com

Sorby 332 Mortise
Chisel, 1/4"
#154358, \$43.50

Mortising chisels sport harder handles and thicker blades in order to withstand the rigors of chopping and prying out chips. A swan-neck chisel can help clean waste from deep mortises.

to remove the material that's typically left after hogging out the waste with a drill press.

Consider adding a swan-neck chisel to complement

your mortiser. This oddly shaped scraping tool can help clean the bottoms of blind mortises, such as those used for locksets or small tenons.

Heavy-Duty Mortisers

Referred to as "framing" or "registered" chisels (depending on the size and shape of the blade), these hefty blades are

designed to take a serious pounding. This type of chisel is essential when tackling large-scale projects such as timber

Heavy-duty mortisers are a perfect match for substantial mortise and tenon joinery. Although designed to stand up to mallet blows, the large chisel can also pare tenon shoulders and cheeks.



Pinnacle Socket Firmer Chisel, 2"
154598, \$132.50

Sorby Corner
Chisel, 3/8"
85S07.03, \$76.50,
leevalley.com

frames and wooden boats. It is also handy for less ambitious projects, such as shaving the walls of larger mortises after removing the waste at the drill press or for cleaning up joints on outdoor projects after using a circular saw. In addition to mortising, a freshly-honed framing chisel can also be enlisted for delicate paring cuts.

When selecting a chisel, look for a socket handle (as on the larger chisel shown). Socket handles are more durable than tang handles and are easier to replace.

A corner chisel makes quick, clean work of squaring up the corners of both deep and shallow mortises. The only downside is that the tool can be tricky to sharpen.

Detail Chisels

Japanese toolmakers produce a wide array of specialty chisels. Cherry-picking a few blades can flesh out any bench chisel set.

For fitting joints and getting into otherwise inaccessible corners, treat yourself to this trio of *push* chisels. As the name suggests, these tools should be hand driven, like the paring chisels below. The long handles offer a comfortable grip for one- or two-handed cuts. The blades are short (for better cutting control) but the long necks extend the reach of the blades so that they're comparable to Western bench chisels.

The angled blades of the takahashi, or skew, chisels make them a great addition to any workshop. Use them for



Bachi Nomi (fishtail), ½"
155904, \$59.00,
japanwoodworker.com

Takahashi (skew), ¼" right
156764, \$52.00
japanwoodworker.com

Takahashi (skew), ¼" left
156903, \$53.00
japanwoodworker.com

The angled ends of these push chisels can reach into corners that are too tight for regular bevel-edge chisels. The fishtail chisel can be used for right and left corners. Skew chisels should be bought as a pair.

paring end grain, trimming tenon shoulders, or cleaning inside corners. Similarly, the flared end of the bachi-nomi,

or fishtail chisel, is handy for getting into tight spots in mortises and blind dovetails, without damaging the side walls.

Paring Chisels

Despite obvious physical differences, paring chisels have one thing in common: they are designed to be driven with hand pressure. These tools can be used for a variety of shaving chores, such as fitting joints, trimming plugs, and removing glue. Selecting the right parer(s) involves balancing convenience and control. For example, the chisel plane and bent paring chisel can be used for similar

chores, but while the smaller plane can sneak into tighter spots, the longer chisel is easier to control (and easier to sharpen). The 9½"-long Narex offers a reach and registration not found when using shorter-bladed bench chisels.

The long handles on some paring chisels enhance control when nestled below the user's shoulder, which allows steering the edge while simultaneously powering through wide shavings.

Paring chisels are intended to make shavings like a plane. Arm yourself with different sizes to accommodate various chiseling challenges.

Narex Paring Chisel, ½"
10S09.84, \$33.00,
leevalley.com

WoodRiver Cranked Neck Chisel Plane Set,
#151240, \$41.99

WoodRiver Bent Paring Chisel, ½"
#157917, \$19.99

Matsamura Paring Chisel, 1½"
#156024, \$141.00,
japanwoodworker.com

Barr Timber Framing Slick, 2½"
#149506, \$192.50



TurnMaster

from *Robert Sorby*
a cut above...

The Robert Sorby TurnMaster is the first tool in the world to combine three cutting edge technologies in one flexible tool.

Cutters are available in tungsten carbide, titanium nitride (TiN) and high speed steel (HSS) providing unsurpassed range to woodturners at every level.



Benefits:

- All cutters interchangeable with one tool
- Unique* indexable cutting head for three scraping options
- Interchangeable cutter head – no need to buy whole new tool
- Flat underside for stability
- High tensile torx screw / key for quick cutter release

*Patent pending

TurnMaster...
the tool with the vision to educate and inspire

CARBIDE: TITANIUM: HSS

Proudly made in Sheffield, England



Robert Sorby,
Athol Road, Sheffield S8 0PA, England.

Tel: 44+ 114 225 0700

Fax: 44+ 114 225 0710

E-mail: sales@robert-sorby.co.uk

Web site: www.robert-sorby.co.uk



TORMEK T-4

Water Cooled Sharpening System



NEW!

ULTIMATE PRECISION SOLID ZINC HEAD



- ✓ Exact replication
- ✓ Fastest Sharpening
- ✓ Cleanest Edges

NEW: Improved design with all core elements in one solid casting.

Add your choice of jigs for the ultimate compact sharpening system!

For more information please visit: www.tormek.com

US Importer: www.affinitytoolworks.com 1-800 586 7635

Glue wood FAST!

Permanent, clear bonds in seconds, not hours

- Repair broken wood pieces • Mount blocks for turning
- Apply a fast, glossy, durable finish • Fix chips in other finishes
- Seal wood to eliminate pinholing • Soak thin stock for hardening
- Fill and stabilize cracks and voids in furniture and pen blanks
- Bonds with finger pressure- no clamping needed

Also bonds metal, plastic, rubber, vinyl, ABS, PVC, and more!

Thin Medium Thick



Trusted by professional woodworkers for decades

Buy direct at CAGlue.com

Or visit your local **WOODCRAFT**

See CAGlue.com for a how-to guide on finishing pens quickly and easily!

Satellite City
(800) 786-0062

Proudly made
in the USA
Since 1970!






Maintain Wood's Natural Beauty With Doctor's Woodshop Finishes

Doctor's Woodshop Finishes are based on three essential principles: wood should look like wood, not plastic, a finish should not obscure the natural beauty of the wood, and a finish should be safe to use. Doctor's Woodshop Finishes contain only one, two or all three of these products – shellac, wax and walnut oil. No solvents, driers or other additives of any kind are used. As a result, the finishes are safe to use, look natural and don't get cloudy.

- 847674** 16 oz. Doctor's Woodshop Walnut Finishing Oil (A)
(Finish Or Sanding Lubricant)
- 855499** 16 oz. Doctor's Woodshop Pens Plus (B)
(Produces Durable, Water-Resistant Shine)
- 843051** 16 oz. Doctor's Woodshop High Build Friction Polish (C)
(New Version – Walnut Oil Replaces Boiled Linseed Oil)
- 855500** 16 oz. Doctor's Woodshop Microcrystal Wax Bowl Finish (D)
(For Lathe Use – Produces A Hard, Shiny Finish That Is Restorable)



Project Photos Courtesy Of: Doctor's Woodshop

Spotlight On Red Oak

America's favorite hardwood

By Pete Stephano

Consultants: Jeff Slahor/Larry Osborn

North America boasts approximately 60 oak species—some with value as timber and others serving no commercial value. Those species we typically find in woodworking fall under the botanical surname *Quercus*, Latin for “a fine tree.” Under this classification, the oaks split into two groups—red and white. The numbers of commercially available red and white species are about even.

Although northern red oak (*Quercus rubra*) is distinct and top-rated for lumber, the wood products industry lumps all red oak (about 8-10 species) together and markets them under that name. In fact, red oak represents around a third of all commercially available hardwood in the United States.

History in woodworking

Practically any wooden item you can imagine has—at one time or another—been fashioned from red oak. It was even a significant factor in America's industrialization, providing everything from barrel staves to plows and railroad ties, steamboats (and their fuel), as well as furniture and flooring. Furnituremakers in particular loved red oak because it was abundant, easily worked, and could be finished in a multitude of ways. That's true today, although red oak also finds its way into flooring, architectural millwork, molding, doors, all types of cabinets, and paneling.

Red oak has a great reputation for wear (abrasion) resistance, but is not ideally suited for outdoor use.

Where the wood comes from

Red oak principally grows from Oklahoma eastward, northward into southern Canada, and as far south as Florida, although there is one timber variety on the West Coast (*Quercus kelloggii*, California black oak).

All in all, you'll find red oak abundant—of the billions of standing board feet of oak sold commercially in this country, over half of it is red.

What you'll pay

Red oak, due to its quantity on commercial timberlands, remains a very moderately priced hardwood. On average, you'll pay about \$3.50 per kiln-dried board foot for flatsawn 4/4 (1") FAS stock. Lesser grades (#1 and #2 Common) cost less, while quartersawn red oak costs more. Traditional 1/2"-thick, plain-sliced red oak veneer costs about \$3 per square foot. A special, more costly, veneer cut called “rift” or “comb” produces straight grain with the appearance of thin lines.

It's a fact that...


- Six states designate a specific oak as their state tree—three in the red oak family. Iowa simply proclaims “oak” as its tree.
- The porous nature of red oak makes it a poor choice for outdoor projects. You can blow air out of a length of red oak much like a straw.



How to select the best stock

Choosing good red oak boards isn't at all difficult. Keep in mind that the heartwood of red oak generally tends to be reddish pink. Although it has a thin band of nearly white sapwood, you'll seldom see it when buying the best grades of lumber. So if you'll be using a clear finish on your project, try choosing boards with similar color. Common red oak grades may have a few knots, but FAS should be relatively knot-free.

Does your plan call for quartersawn wood? Some sawmills cut and carry such boards. As with white oak, look for the characteristic ray flecks.



Working red oak in the shop

Be prepared: Freshly sawn red oak usually has a sour, often unpleasant odor. But that's about its only negative. Due to red oak's large vessels in the earlywood and smaller vessels in the latewood of each growth ring, it features a coarse, open-grain texture. Also, it machines easily with less burning than hard maple. Try the following tactics for milling success.

- **Ripping and routing.**

Use a sharp blade when ripping red oak for a clean, crisp edge. Feed wood at a moderate rate into the table saw blade—too slow and it will burn. This applies to routing, too. If you do end up with burns, expect more sanding.

Shallow passes with a router bit counter red oak's tendency to splinter, especially on end grain. As always, it's good policy to employ a backing board.

- **Jointing.** Joint flatsawn red oak with the knives rotating in the direction of the grain. This prevents gouging the wood's surface or edge.



- **Assembling.** Keep in mind that red oak's tannin content in contact with the moisture in glue squeeze-out and steel from clamp jaws or bars can create an ugly black stain on the wood. Protect the wood in the clamping areas with waxed paper. With screws, drill pilot holes to prevent splitting.
- **Sanding.** When sanding red oak, be careful that you don't remove more of the softer earlywood than the harder latewood, resulting in depressions that show up under a finish. Otherwise, the wood sands without a problem. Avoid abrading with steel wool as steel fibers tend to lodge into the grain and can later rust.



Deciding on the right finish

Many woodworkers like the contemporary look of unstained red oak. That's simple enough because all clear film finishes work well if applied in thin coats and sanded in between.

But staining is a whole other story. Why? Red oak's large-pored earlywood (in flatsawn boards) soaks up pigment, resulting in darker areas that accentuate the wood's coarseness. What can you do? One option is to fill all the pores with a paste-type filler. The filled wood yields a less dramatic grain contrast. The result is smoother, and it takes fewer coats to build the final finish. A pickled finish offers a different way to go.

Another option: use any kind of aniline dye. It penetrates

evenly, with one exception—the ray flecks of quartersawn red oak won't absorb as much. That's okay, though; they really need to stand out. ■

Red Oak Quick Take

Cost	Moderate
Weight	Moderate/heavy
Hardness	High
Stability	High (when dry)
Strength	Moderate/high
Durability	Very high (indoors)
Toxicity	None
Tool Type	Hand and carbide-tipped power tools
Common Uses	Cabinets, doors, flooring, furniture, millwork, moldings

Red oak finishing tips

- Any type of dye for wood will do, but the water-soluble kind won't color the pores as well. You can, though, add a pigment stain over the dye and wipe off the excess for even color.
- Again, for even color, you also can seal the wood with a thinned mixture of shellac, and then add a finish coat toned with either a pigment or dye.
- For the adventuresome: Use a colored wood filler or glaze to take advantage of red oak's large earlywood pores. It'll create a striking contrast with the denser latewood.

BUILD YOUR OWN KNIFE JUST ADD WOOD

NEW

DESK KNIFE/ LETTER OPENER KIT
w/ Leather Sheath
\$19.99
WC#157858

DROP POINT KIT
w/ Leather Sheath
\$20.99
WC#84445

SEMI-SKINNER KIT
w/ Leather Sheath
\$20.99
WC#84445

Kit includes everything (hardwood sold separately)

(Finished example)

FOLDER KITS also available

LINER-LOCK FOLDER BLADE KIT
2" Blade
4 7/8" Overall
\$11.99
WC#153378

LINER-LOCK FOLDER BLADE KIT
3 1/4" Blade
4 5/8" Overall
\$17.99
WC#153377

(Finished example)

Available at a Woodcraft store near you or visit woodcraft.com



SARGE
KNIVES

(Prices subject to change)

Ad Index

PRODUCT Website Page

Adhesives

Nexabond	www.nexabond.com	66
Satellite City	www.caglue.com	72
Titebond	www.titebond.com/TBIIIvsPolyurethane	OBC

Bits, Blades, & Cutters

Forrest Mfg.	www.forrestblades.com	15
Freud	www.freudtools.com/premierfusion	IFC
PS Wood	www.pswood.com	78
Whiteside Machine	www.woodcraft.com	7

Carving

King Arthur's Tools	www.katools.com	9
Saburr Tooth	www.saburrtooth.com	67

Dust Collection

Oneida	www.oneida-air.com	17 & 77
--------	--	---------

Hand Tools

Thomas Flinn & Co.	www.flinn-garlick-saws.co.uk	67
--------------------	--	----

Moisture Meters

Lignomat	www.wood-moisture.com	12
----------	--	----

Power Tool Accessories

Kreg	www.kregtool.com	19
------	--	----

Power Tools

Epilog Laser	www.epiloglaser.com/woodcraft	16
Grizzly	www.grizzly.com	2 & 3
Laguna Tools	www.lagunatools.com	1
Norwood	www.norwoodsawmills.com	18
Rikon	www.rikantools.com	IBC
Sawstop	www.sawstop.com/10	5

School/Instruction

CT Valley School of WW	www.schoolofwoodworking.com	66
The American Woodshop	www.wbgu.org/americanwoodshop	19

Turning Supplies

Berea Hardwoods	www.woodcraft.com	66
Easy Wood Tools	www.easywoodtools.com	20
Ring Master	www.ringmasterlathe.com	78
Robert Sorby	www.robert-sorby.co.uk	72

Wood & Veneers

American Specialty Hardwoods	www.americanspecialtyhardwoods.com	79
Cook Woods	www.cookwoods.com	77
Northwest Bamboo	www.nwbamboo.com	78
West Penn Hardwoods	www.westpennhardwoods.com	78
Woodfinder	www.woodfinder.com	78

Woodworking Supplies

Armor	www.ARMOR-Tool.com	29
Blokkz	www.blokkz.com	79
Brand-First	www.brand-first.com	78
Create-A-Bed	www.wallbed.com	79
Fortune	www.woodcraft.com	68
Fred Wissen Designs	www.pownsubbie.com	78
General Tools	www.woodcraft.com/generaltools	10 & 11
Leigh	www.leighjigs.com	14
National Hardware	www.natman.com	78
Richard L. Greenwald	www.richardlgreenwald.com	79
Royal Wood Ltd.	www.royalwoodltd.com	79
Rustoleum	www.rustoleum.com	21
Sarge	www.woodcraft.com	76
Sjoberg	www.sjobergs.se	67
Starrett	www.starrett.com	50
Touchstone Home Products	www.touchstonehomeproducts.com	13
Touch-Up Solutions	www.weare@touchupsolutions.com	78
Tormek	www.tormek.com	72
Woodcraft Franchise	www.woodcraftfranchise.com	23
Woodcraft Magazine	www.woodcraft.com/10ksweeps	28
Woodcraft Supply	www.woodcraft.com	73 & 80



World's Best Selection of Exotic Turning Wood and Lumber

www.cookwoods.com
1-877-672-5275

Turn Ordinary Dust Collection into Extraordinary Dust Collection!



Super Dust Deputy®
Super Dust Deputy XL®

Collector Not Included.

Shown with optional drum and hoses.

U.S. Patent #7,282,074
Design Pat. #D703,401

99%+ of Dust Here.

- New innovative cyclone design separates 99%+ of wood waste before the filter. Helps maintain consistent airflow.
- Retrofits to single stage 1/2hp to 5hp dust collectors.
- Compact size. Static dissipative plastic.



Dust Deputy® Deluxe

Clean Air to Vacuum

Dust In

99% of Dust Here

Vacuum Not Included

U.S. Patent #7,282,074

- Cyclone design separates 99%+ of wood waste before the filter. Helps maintain consistent airflow.
- Pays for itself in filter replacement costs alone!
- Retrofits to any shop vacuum and can be used wet or dry!

Other Dust Deputy® models available. Check online.

Like

Call Today for Information!
1.800.732.4065

Oneida Air Systems
Dust Collection Systems and Components Since 1993.

FREE Catalog Online!
www.oneida-air.com

The Market

BRAND-FIRST
Electric, Flame Heated, & Propane Powered
Branding Tools with a Logo, Signature, or
Standard Image. Specials Starting at \$74.00
Orders in by December 15th
Guaranteed for Christmas Delivery!



Ph: (248)583-5353 Fx: (248)588-0051
Sales@Brand-First.com www.Brand-First.com

**NORTHWEST
BAMBOO** Inc
DIMENSIONAL LUMBER,
COUNTERTOPS,
VENEERS, PLYWOOD
503-695-3283
WWW.NWBAMBOO.COM

**Timber Wolf
Band Saw
Blades**

- *Precision milled teeth
- *High-ductile steel
- *Any length available
- *True tracking
- *Low-tension
- *Thin kerf
- *Remarkable turns
- *Warranted welds
- *Electro-heat induction hardened
- *Double tempered weld



Celebrating 20 yrs
www.pswood.com
1-800-939-4414

NAILS, TACKS & BRADS
NOW AVAILABLE AT WOODCRAFT



National Hardware has everything you need to complete your woodworking project.

18072 800.346.9445

**WEST PENN
HARDWOODS, INC.**

EXOTIC WOOD WONDERLAND!

The Largest Importer of
Exotic Hardwoods From
Pen Blanks to the Whole Log!

Check out our HUGE slab inventory
Turning Wood * Pen Blanks * Unique Boards Lumber
Thin-Dimensioned Lumber * Burls * Bottle Stoppers
Bowl Blanks * Peppermill Stock * Guitar Sets
Luthier Wood Combo Pack Deals * Live Edge Flitches
...and much, much more!!

USE COUPON CODE WJ10 TO RECEIVE
10% OFF YOUR ONLINE ORDER

www.westpennhardwoods.com
230 S. Clinton St., Olean, NY 14760
716-373-6434
support@westpennhardwoods.com



**Touch Up
Solutions**



Wood Touch-Up & Repair Products
Stocked & Serviced at your local
WOODCRAFT

Buying *locally* will save you time & money with
NO shipping & handling cost!

Woodcraft Customer Service: 1-800-535-4482

For a Complete Catalog
Please call or email us today
Tel: 1.877.346.4747
TUS e-mail: wecare@touchupsolutions.com

 You Tube

CUSTOM PEN BLANKS & SILICONE MOLDS



We design a wide variety of handcrafted pen blanks
or you can use our molds to create your own!

Fred Wissen Designs LLC - PTownSubbie.com

Ring Master
Boards to Bowls in Minutes



Easily make bowls, vases, toys, or any round hollow project
The secret of segmented bowl turners for over 30 years

www.ringmasterlathe.com

Pssst! NEED WOOD?

woodfinder®


Now over 400
suppliers! It's fast, easy
and FREE!

www.woodfinder.com

SUPPLIERS: CALL TOLL-FREE 1-877-933-4637 TO JOIN US!

ADVERTISE IN The Market

Contact: **Kiah Harpool**
at **(304) 865-5268**
or e-mail at:
Kiah_Harpool@
woodcraftmagazine.com



WWW.RICHARDLGREENWALD.COM
USE PROMO CODE "WDCRT" AT CHECKOUT TO RECEIVE 10% OFF

Seat Weaving Supplies Chair Cane & Splint Shaker Tape Fiber & Natural Rush Complete Line of Basket Weaving Supplies



Royalwood Ltd.
517 WC Woodville Rd.
Mansfield, Ohio 44907
800-526-1630
www.RoyalwoodLtd.com

www.blokkz.com

Unique tools for
woodworkers



Universal Clamping Blocks (UCBs)
Easily clamp a wide variety of joints



Woodworker's Centering Punch
Fast, easy & accurate center punching

Need more space?
Build your own
murphy bed.



Piston-lift
mechanism kit
includes
step-by-step
construction plans
and instructional
DVD

Create-A-Bed®
Toll Free **1-877-966-3852**
www.wallbed.com

United States Postal Service Statement of Ownership, Management, and Circulation

1. Publication Title **Woodcraft Magazine** 2. Publication Number **024-953**
3. Filing Date **9/30/2014** 4. Issue Frequency **Bi-Monthly: Dec/Jan,**
Feb/March, April/May, June/July, Aug/Sept, Oct/Nov 5. Number
of Issues Published Annually **6** 6. Annual Subscription Price **\$19.97**
7. Complete Mailing Address of Known Office of Publication **Woodcraft**
Magazine 4420 Emerson Ave, Suite A Parkersburg, WV 26104
8. Complete Mailing Address of Publisher **Woodcraft Supply LLC**
P.O. Box 1686 Parkersburg, WV 26102 9. Full Names and Complete
Mailing Addresses of Publisher **Gary Lombard 4420 Emerson Ave,**
Suite A Parkersburg, WV 26104; Editor Jim Harrold 4420 Emerson
Ave, Suite A Parkersburg, WV 26104; 10. Owner Woodcraft Supply
LLC P.O. Box 1686 Parkersburg, WV 26102 11. Known Bondholders,
Mortgagees, and Other Security Holders Owning or Holding 1 Percent
or More of Total Amount of Bonds, Mortgages or Other Securities.
None 12. Tax Status The purpose, function, and nonprofit status of this
organization and the exempt status for federal income tax purposes:
has Not Changed During Preceding 12 Months 13. Publication
Title **Woodcraft Magazine** 14. Issue Date for Circulation
Data Below **A/S 2014**

15. Extent and Nature of Circulation

Average No. Copies Each Issue During Preceding 12 Months:

a. Total Number of Copies (Net press run):	130,686
b. Paid Circulation (By Mail and Outside the Mail)	
(1) Mailed Outside-County Paid Subscriptions Stated on PS Form 3541. (Include paid distribution above nominal rate, advertiser's proof copies, and exchange copies):	99,294
(2) Mailed In-County Paid Subscriptions Stated on PS Form 3541 (Include paid distribution above nominal rate, advertiser's proof copies, and exchange copies):	0
(3) Paid Distribution Outside the Mails Including Sales Through Dealers and Carriers, Street Vendors, Counter Sales, and Other Paid Distribution Outside USPS:	5,700
(4) Paid Circulation by Other Classes Mailed Through the USPS (e.g. First-Class Mail):	0
c. Total Paid Distribution [Sum of 15b. (1) (2), (3), and (4)]:	104,994
d. Free or Nominal Rate Distribution (By Mail and Outside the Mail)	
(1) Free or Nominal Rate Outside County Copies included on PS Form 3541:	7,935
(2) Free or Nominal Rate In-County Copies Included on PS Form 3541:	0
(3) Free or Nominal Rate Copies Mailed at Other Classes Through the USPS (e.g. First-Class Mail):	0
(4) Free or Nominal Rate Distribution Outside the Mail (Carriers of other means):	83
e. Total Free or Nominal Rate Distribution [Sum of 15d. (1), (2), (3), and (4)]:	8,019
f. Total Distribution (Sum of 15c. And 15e.):	113,012
g. Copies not Distributed:	17,673
h. Total (Sum of 15f. And 15g.):	130,686
i. Percent Paid (15c. Divided by 15f. times 100)	92.9%
No. Copies of Single Issue Published Nearest to Filing Date	
a. Total Number of Copies (Net press run):	130,508
b. Paid Circulation (By Mail and Outside the Mail)	
(1) Mailed Outside-County Paid Subscriptions Stated on PS Form 3541. (Include paid distribution above nominal rate, advertiser's proof copies, and exchange copies):	99,994
(2) Mailed In-County Paid Subscriptions Stated on PS Form 3541 (Include paid distribution above nominal rate, advertiser's proof copies, and exchange copies):	0
(3) Paid Distribution Outside the Mails Including Sales Through Dealers and Carriers, Street Vendors, Counter Sales, and Other Paid Distribution Outside USPS:	5,400
(4) Paid Circulation by Other Classes Mailed Through the USPS (e.g. First-Class Mail):	0
c. Total Paid Distribution [Sum of 15b. (1) (2), (3), and (4)]:	105,344
d. Free or Nominal Rate Distribution (By Mail and Outside the Mail)	
(1) Free or Nominal Rate Outside County Copies included on PS Form 3541:	7,806
(2) Free or Nominal Rate In-County Copies Included on PS Form 3541:	0
(3) Free or Nominal Rate Copies Mailed at Other Classes Through the USPS (e.g. First-Class Mail):	0
(4) Free or Nominal Rate Distribution Outside the Mail (Carriers of other means):	0
e. Total Free or Nominal Rate Distribution [Sum of 15d. (1), (2), (3), and (4)]:	7,806
f. Total Distribution (Sum of 15c. And 15e.):	113,150
g. Copies not Distributed:	17,358
h. Total (Sum of 15f. And 15g.):	130,508
i. Percent Paid (15c. Divided by 15f. times 100)	93.1%

16. Publication of Statement of Ownership

Will be printed in the Dec/Jan 2015 issue of this publication.


17. Signature and Title of, Publisher, Gary Lombard, 4420 Emerson Ave, Suite A Parkersburg, WV 26104 Date: 10/1/113. I certify that all information furnished on this form is true and complete. I understand that anyone who furnishes false or misleading information on this form or who omits material or information requested on the form may be subject to criminal sanctions (including fines and imprisonment) and/or civil sanctions (including civil penalties).



American Specialty Hardwoods is wishing *Woodcraft Magazine* customers a Merry Christmas and a Happy New Year!

American Specialty Hardwoods provides high quality figured wood from Michigan, like tone woods, live edge table tops, and craft woods for craftsmen, luthiers, and artisans.

- Curly or flame soft maple
- Spalted wood
- Hard maple
- Walnut
- Cherry



Visit us today to see what we can do for you at
www.AmericanSpecialtyHardwoods.com
or contact our sales manager, Jerry, at
(517) 403-3586

WOODCRAFT®

Since 1928, Woodcraft has been committed to providing quality tools, supplies and advice to our customers. From providing in-store classes and demonstrations to funding educational woodworking programming, Woodcraft has remained steadfast in our commitment to the beginner, intermediate and experienced woodworker for over 80 years running.

The American Woodshop

www.wbgu.org/americanwoodshop

Woodcraft is pleased to continue sponsorship of *The American Woodshop* with Scott and Suzy Phillips, now in its 22nd season on PBS.

Season 22 – “Scott And Suzy – Bringing It Home”
Fantastic Home Accents – Hand Skill Builders
13 episodes with woodworking tips for every skill level.

Techniques include: turning, joinery, tool tune-ups, making jigs, bench building, furnituremaking and cabinetmaking! It's Tool Time!!!

Join Scott and Suzy to get the most out of your woodshop tools!



ROUGH CUT

WOODWORKING WITH TOMMY MAC

www.thomasjmacdonald.com

We are also proud to provide major funding for the two-time Daytime Emmy® Award-nominated public television series and recipient of four Telly Awards, *Rough Cut – Woodworking with Tommy Mac*.

Season Five projects include: Patio Prep Station, Arts & Crafts Rocking Chair, Pencil Post Bed, Windsor Chair, Simple Shaker Night Stand And Finishes, Linen Press, Pt. 1 And Pt. 2, Hall Tree And Bench, Queen Anne Table, Shaker Style Clock, Gate Leg Table, Frank Lloyd Wright-Inspired Light Pendants and China Cabinet.



Photo ©
Anthony Tieuli
for WGBH
Educational
Foundation

Rob Cosman


“YOUR HAND TOOL COACH”

www.RobsWorkshop.com

Woodcraft is privileged to partner with Rob Cosman, “Your Hand Tool Coach,” featured on the educational RobsWorkshop.com.

Rob Cosman's daily online episodes teach the proper use of hand tools and power tools in a motivational and educational way. Hand-tool demonstrations are Tuesdays and Thursdays, and power tools are demonstrated Mondays, Wednesdays and Fridays.

Purchase any WoodRiver® Hand Plane and get A FREE 3 Month Subscription to Rob Cosman's Interactive Online Hand & Power Tool Workshops! The Subscription is Seventy-Five 30-Minute Sessions As Well As Access to Over 800 Previous Episodes... Plus Access to Hand Plane 101 – A \$120 Value!



Woodcraft® And Tool Box™ By Woodcraft® Stores In Your Area:

Alabama

Birmingham/Pelham:
205-988-3600

Arizona

Phoenix/Chandler:
480-539-9663
Tucson:
520-742-9663

California

Orange County/
Fountain Valley:
714-963-9663
Sacramento:
916-362-9664

San Carlos:
650-631-9663
Ventura:
805-658-9663

Colorado

Colorado Springs:
719-266-9889
Denver:
303-290-0007
Loveland:
970-292-5940

Connecticut

Hartford/Manchester:
860-647-0303
Norwalk:
Woodworker's Club
203-847-9663

Delaware

Wilmington/New Castle:
302-323-0400

Florida

Jacksonville:
904-721-9796
Orlando:
407-260-5002
Tampa/Clearwater:
727-532-6888

Georgia

Atlanta:
770-587-3372

Hawaii

Honolulu:
808-841-9876

Idaho

Boise:
208-338-1190

Illinois

Woodridge:
630-435-9663

Indiana

Indianapolis:
317-578-3400

Kansas

Kansas City/Lenexa:
913-599-2800

Kentucky

Lexington:
859-231-9663

Louisville:

502-671-0900

Maryland

Rockville:
Woodworker's Club
301-984-9033

Massachusetts

Boston/Woburn:
781-935-6414

Boston – Walpole:
508-668-2413

West Springfield:
413-827-0244

Michigan

Detroit Area:
Canton:
734-981-6808
Sterling Heights:
586-268-1919

Grand Rapids:
616-957-9663

Saginaw:
989-249-6662

Minnesota

Minneapolis/
Bloomington:
952-884-3634

Missouri

St. Louis/
Maryland Heights:
314-993-0413

New Hampshire

Portsmouth/Newington:
603-433-6116

New York

Rochester:
585-292-9690

North Carolina

Charlotte/Matthews:
704-847-8300

Raleigh:
919-781-1911

Ohio

Cincinnati:
513-407-8371

Cleveland/
Oakwood:
440-232-7979

Columbus:
614-273-0488

Dayton:
937-438-1282

Toledo:
419-389-0560

Oklahoma

Oklahoma City:
405-748-8844
Tulsa:
918-384-0100

Oregon

Eugene:
541-685-0677

Portland/Tigard:
503-684-1428

Pennsylvania

Allentown:
610-351-2966

Harrisburg:
717-409-8173

Philadelphia/
Downingtown:
610-873-5660

South Carolina

Greenville:
864-627-8760

Tennessee

Chattanooga:
423-710-8001

Knoxville:
865-539-9330

Nashville:
615-599-9638

Texas

Austin:
512-407-8787

Dallas/Addison:
972-422-2732

Fort Worth:
817-334-1025

Houston:
281-880-0045

South West Houston:
281-988-9449

San Antonio:
210-545-5885

Utah

Salt Lake City/
South Jordan:
801-566-5652

Virginia

Leesburg:
703-737-7880

Norfolk:
757-466-1166

Richmond:
804-355-3945

Roanoke:
540-366-7144

Springfield:
703-912-6727

Washington

Seattle:
206-767-6394

Spokane:
509-892-9663

West Virginia
Parkersburg:
304-485-4050

Wisconsin

Appleton/Fox Cities:
920-730-9663

Madison:
608-273-8868

Milwaukee/New Berlin:
262-785-6770

QUALITY WOODWORKING TOOLS • SUPPLIES • ADVICE®

For A Free Catalog Or To Find Your Local Woodcraft Store, Visit woodcraft.com Or Call 800-225-1153. 15WD01P

RIKON

PRO TOOLS FOR EVERYONE



"Looking for that perfect gift? Everyone loves Power Tools."

NEW

MIDI VSR Lathe

Redesigned for the serious Woodturner. Features a robust 1 HP Motor, 12-1/2" Swing, 20" Working Distance between Centers and convenient Control Center with ON/OFF, Forward-Reverse Switch, Variable Speed Dial and LED RPM Display.



BANDSAWS



10-325

14" Professional Bandsaw

The ideal saw for the novice or pro. Ample 13" depth of cut with 13-5/8" throat can handle most of your bandsawing needs. Features micro adjustable ball bearing guides, 1-1/2 HP motor and quick release blade tension mechanism.



10-341

18" Bandsaw

Features full 13" depth of cut and 17-1/2" throat for excellent resawing capabilities. With a large 19" x 17" work table and powerful 2 HP, 220V motor

NEW

6" x 48" Belt/10" Disc Sander

Versatile 1 HP Sander will handle all your surfacing needs. 6" x 48" Belt sands in horizontal or verticle position. 10" Disc tackles precision edge sanding from 90° to 45° angles.



STAND INCLUDED



www.rikontools.com

The facts are hard to ignore.

Titebond® III outperforms polyurethane glues.

Reference Guide

Glue comparison

What woodworkers need to know!

	Titebond III	Polyurethane Glues
Higher Bond Strength	✓	✓
Exterior Use – Waterproof	✓	
Easy Water Cleanup	✓	
Much Safer To Use	✓	
Shorter Clamp Time	✓	
No Foam – Less Mess	✓	
Shorter Open Time	✓	✓
Doesn't Stain Skin	✓	✓
Bonds Most Materials	✓	
Bonds Oily / Exotic Woods	✓	
Lower Cost – Better Value	✓	
Longer Usable Shelf Life	✓	

Woodworking Handbook

Titebond III
ULTIMATE
Wood Glue
Rated #1 By Pros
Waterproof
Exterior/Interior
Superior strength
Longer assembly time
Water cleanup
NET 8 FL. OZ. (237 mL)

As the leader in wood glues, we want you to know the truth about polyurethane glue and woodworking. A straightforward comparison between Titebond® III Ultimate Wood Glue and polyurethane glue tells the story.

Titebond® III is THE ultimate choice for bonding wood to wood. Period.



www.titebond.com/TBIIIvsPolyurethane

